



- Material**
- Terminal body (metal housing): Brass stamped
 - Terminal screw: Steel Zinc plating"-slot type
 - Wire guard: Stainless steel
 - Surface of solder tail: Tin plated
 - Insulator (housing): Thermoplastic (UL94V-0), Grey

- Electrical UL/ cUL**
- Voltage rating: 300VAC/250VAC
 - Current rating: 10A/15A
 - Wire range:
 - Solid wire(AWG): 12-22/12-20
 - Stranded wire(AWG):12-22/12-20
 - Torque(Lb-In): 3.5
 - Screw:M2.5
 - Wire strip length:6-7mm
 - Withstanding Voltage: 1.6KV/1.5KV
 - Operating temperature: -30°C to +105°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval:

N= NUMBER OF CONCATS

RoHS compliant
Unit: mm



File No.: E349947

Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	12.05.2009	Dean
X.	±0.50					Approved	18.04.2016	Joanna
X.X	±0.30							
X.XX	±0.10							
DIM	TOL	②	Add UL	18.04.2016	Joanna	ASSMANN WSW/ components		
X.°	±1°	①	Drawn	12.05.2009	Dean			
Angle	TOL	Id.	Modification	Date	Name	Replace	ASS 3513 CO	rev02

Customer-No.	
ASSMANN WSW-No. A-TB500-TKxxSB	
Drawing-No.	rev02
Replace	Sheet