

VIEW ON MATING SIDE

○	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
△	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
○	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1			

A = 16 STANDARD CONTACTS L = 3
 B = 16 STANDARD CONTACTS L = 3
 C = 16 STANDARD CONTACTS L = 3
 S = 48 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G1/O = CONTACT AREA LEVEL1 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	YES
DIMENSIONS	SD-85003-0011 SHT I-I

C	G1/O	c1-16
B	G1/O	b1-16
A	G1/O	a1-16
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

RoHS COMPLIANT

ENTER DESCRIPTION ELC.MC1.12006-0807 DRWNGSATTI/MARAD 2006/05/05 CHKD:SSUDHIR 2006/05/08 APPR:SSUDHIR 2006/05/08	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		4 PLACES ±---± 3 PLACES ±---± 2 PLACES ±---± 1 PLACE ±---±	.mm INCH ±---± ±---± ±---± ±---±	DRAWN BY SHANKAR	DATE 2006/05/04	TITLE 48 POS. MALE CONNECTOR ACC. DIN 41612 STYLE C/2 CONTACTS ARRANGEMENT			
		ANGULAR ±---°		CHECKED BY SSUDHIR	DATE 2006/05/04	MOLEX INCORPORATED			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY SSUDHIR	DATE 2006/05/04	MATERIAL NO. 85003-1859	DOCUMENT NO. SD-85003-1859	SHEET NO. 1 OF 1	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION