



MATERIAL NUMBER	OLD PART NUMBER	FINISHED LENGTH
1201140057	BTY6030-FBA	-

VOLTAGE RATING	10-30 VDC
AMPERAGE RATING PER PORT	4 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	-25°C TO 90°C
UL CERTIFICATIONS	UL RECOGNIZED, FILE NO. E46237
CSA CERTIFICATIONS	CSA CERTIFIED, FILE NO. LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
2	O-RING	VITON	RED
3	RECEPTACLE SHELL	BRASS	NICKEL PLATED
4	HOUSING	PBT	YELLOW
5	LABEL	ABS	WHITE
6	LENS	NYLON	CLEAR

ADDED BRK, REMVD SHORT EC NO: WEU2010-0463 DRWN: LHARTMAN 2012/01/25 CH'KD: TWOLDEGE APPR: JFMURPHY	QUALITY SYMBOL ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 1:25.4	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		4 PLACES ±--- mm ±--- INCH 3 PLACES ±--- mm ±--- INCH 2 PLACES ±--- mm ±0.1 INCH 1 PLACE ±0.3 mm ±--- INCH	DRAWN BY DATE LHARTMAN 2012/01/25		TITLE MICRO-CHANGE MPIS 6 PORT PNP TWIN PORT 5P FIELD ATTACHABLE		MOLEX INCORPORATED		SHEET NO. 1 OF 1
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART		DOCUMENT NO. SD-120114-078		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			