THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART #	STUD SIZE		DIMENSIONS in. [mm]				
	ENGLISH	METRIC	L ± .03 [0,76]	W ± .01 [0,25]	C ± .02 [0,51]	M ± .03 [0,76]	H ± .01 [0,25]
E10-6RB	#6	M3	.78 [19,8]	.31 [7,9]	.31 [7,9]	.62 [15,8]	.15 [3,8]
E10-8RB	#8	M4	.78 [19,8]	.31 [7,9]	.31 [7,9]	.62 [15,8]	.17 [4,3]
E10-10RB	#10	M5	.81 [20,6]	.38 [9,7]	.31 [7,9]	.62 [15,8]	.20 [5,1]
E10-14RB	1/4"	M6	.96 [24,4]	.52 [13,2]	.38 [9,7]	.70 [17,8]	.27 [6,9]



NOTES:
1. USED FOR:
   A. 12-10 AWG [4,0-6,0 mm²] SOLID OR STRANDED COPPER WIRE
   B. 302°F [150°C] MAX. TEMP. RATING
   C. 2000V MAX VOLTAGE

2. MATERIAL:
   A. STAMPING: .04" [1,0] THK COPPER, TIN PLATED

3. INSTALLATION TOOLS:
   A. UL LISTED AND CSA CERTIFIED:
      CT-100A, CT-200, CT-600-A (CT-570CH)
      CT-1570, CT-1701, CT-2500(CT-2570CH)
   B. PANDUIT APPROVED: CT-160, CT-260

4. WIRE STRIP LENGTH: 9/32" $^{+1/32}_{-0}$ [7,1mm $^{+0,8}_{-0}$]

5. SEE www.panduit.com FOR PACKAGE QUANTITIES INDICATED BY PART NUMBER SUFFIX

6. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT

LISTED 587H E52164

CERTIFIED LR31212

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
00	2/18	JHNU	TMR	RGB	RELEASED	00123SH

TITLE
STRONGHOLD RING TERMINALS NON-INSULATED, BUTTED SEAM #12-10 AWG
CUSTOMER DRAWING

ITEM REVISION NAME: 00123STC/00

DATASET FILE NAME: 00123STC_DC/00

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]
.x ± .1 [2.54] .xxx ± .005 [.13]
.xx ± .01 [.25] ANGLES ± 5 °
THIRD ANGLE PROJECTION

MATERIAL: SEE NOTES

DRAWING NUMBER: SH41188

DRAWN BY	DATE	CHK	SCALE	SIZE
JHNU	2/18	TMR	N.T.S.	A

SHEET 1 OF 1

D10100DA/12