

An underwater remote-operated vehicle (ROV) is shown in a deep-sea environment. The ROV is a complex piece of machinery with various sensors, cameras, and mechanical components. It is positioned in the center-left of the frame, angled towards the right. The background is a dark, blue-green underwater scene with some rocky structures and bubbles. The overall image has a blue color cast, particularly in the lower right quadrant where the text is located.

# xsens

## MTi 10-series

The reliable industry standard for  
MEMS based IMU, VRU and AHRS



### MTi 10-series

- Industry-proven, cost-effective MEMS based orientation sensor
- Full-featured sensor fusion algorithm with easy to use SDK
- 3 integration levels available: IMU, VRU and AHRS

## Product Overview

	MTi-10 IMU	MTi-20 VRU	MTi-30 AHRS
Calibrated Sensor Data	yes	yes	yes
Roll/pitch (Static)	-	0.2°	0.2°
Roll/pitch (Dynamic)	-	0.5°	0.5°
Yaw	-	Active Heading Stabilization (AHS)	1.0°

### Proven Xsens sensor fusion algorithm

- Superior heading tracking using Active Heading Stabilization (AHS)
- In-run Compass Calibration (ICC)
- XKF3 sensor fusion algorithm trusted by highprofile customers
- Selectable filter profiles for range of applications

### Easy software integration

- Extensive suite of configurable output formats, calculated onboard the MTi
- MT Software Suite with intuitive GUI
- Complete SDK for all operating systems
- Support for Robotic Operating System (ROS)
- Xsens Xbus protocol or ASCII (NMEA)
- Access to BASE (by Xsens), an extensive knowledge base and community forum

### Excellent hardware design

- High quality industrial grade components
- Signal processing pipeline, optimized for industrial applications
- Low latency for real-time applications
- 10 kHz simultaneous sampling, 2 kHz SDI algorithm with coning/sculling compensation
- Wide array of synchronization options

### Specification highlights

- Available as IP67 encased MTi or OEM board
- Choice of several interfaces and onboard USB
- All Xsens products are fully interchangeable
- Cost-effective system integrator solution

## Sensor specifications

	Gyroscopes	Accelerometers
Standard full range *	+/- 450 °/s	+/- 20 g
Initial bias error	0.2 °/s	5 mg
In-run bias stability	18 °/h	15 µg
Bandwidth (-3 dB)	415 Hz	375 Hz
Noise density	0.03 °/s/√Hz	60 µg/√Hz
g-sensitivity (calibrated)	0.006 °/s/g	N/A
Non-orthogonality	0.05 deg	0.05 deg
Non-linearity	0.03%	0.1%

	Magnetometer
Standard full range	+/- 8 G
Total RMS noise	0.5 mG
Non-linearity	0.2%
Resolution	0.25 mG

\* Optional +/- 1000 °/s available on request.

## System specifications

Input voltage	4.5 to 34V or 3V3
Typical power consumption	550 mW @ 5V
IP-rating	IP67 (encased)
Temperature (in use)	-40 to 85 °C
Casing material	Anodized aluminum 6082
Sampling frequency	10 kHz/channel (60 kS/s)
Clock drift	10 ppm or external reference
Output frequency	Up to 2 kHz


Interfaces	RS232/RS422/RS485/USB/UART
Latency	<2 ms
Sync options	SyncIn, SyncOut, Clock sync
Interface protocol	Xbus or ASCII (NMEA)
Mounting orientation	No restriction, full 360° in all axes
Built-in self test (BIT)	Gyroscopes, accelerometers, magnetometer
MTBF	141,000h



MTi 10-series Development Kit: MTi, software and cabling



MTi encased: 57x42x23.5 mm, 52g, 9-pins push-pull connector



MTi OEM: 37x33x12 mm, 11g, 16-pins header



## ABOUT XSENS

Xsens is the leading innovator in 3D motion tracking technology and products. Its sensor fusion technologies enable a seamless interaction between the physical and the digital world in applications such as industrial control and stabilization, health, sports and 3D character animation. Clients and partners include Electronic Arts, NBC Universal, Daimler, Autodesk, ABB, Siemens and various other leading institutes and companies throughout the world. Xsens is part of mCube, the provider of the world's smallest MEMS motion sensors, key enablers for the Internet of Moving Things. Xsens has offices in Enschede, Los Angeles, Shanghai and Hong Kong.

Visit [xsens.com/distributors](http://xsens.com/distributors) for an overview of Xsens' worldwide distributor network



### Xsens Netherlands

Xsens Technologies B.V.  
P.O. Box 559  
7500 AN Enschede  
The Netherlands

Phone: +31 88 97367 00  
Fax: +31 88 97367 01  
Email: [info@xsens.com](mailto:info@xsens.com)

### Xsens North America Inc.

101 N. Pacific Coast Hwy,  
Suite 306  
El Segundo, CA 90245  
North America

Phone: 310-481-1800  
Fax: 310-416-9044  
Email: [info@xsens.com](mailto:info@xsens.com)

### Xsens AsiaPac

Unit 208, Bldg 16W  
Hong Kong Science Park  
Shatin  
Hong Kong

Phone: +852 3618 9080  
Fax: +852 3705 8994  
Email: [info@xsens.com](mailto:info@xsens.com)

Building 1, 2nd Floor  
No.333 Huangqing Road  
PRC 201899  
Shanghai

Phone: +86 021 31760067  
Fax: +86 021 31760067  
Email: [china@xsens.com](mailto:china@xsens.com)

© 2005-2020, Xsens Technologies B.V. All rights reserved. Information in this document is subject to change without notice. Xsens, MTI and MTI-G are registered trademarks or trademarks of Xsens Technologies B.V. and/or its parent, subsidiaries and/or affiliates in The Netherlands, the USA and/or other countries. All other trademarks are the property of their respective owners.

Unless stated otherwise, all specifications are typical. Specifications subject to change without notice.  
© Xsens, February 2020



[www.xsens.com](http://www.xsens.com)