

ÖLFLEX® HEAT 260 SC

For use in the most extreme conditions

ÖLFLEX® HEAT 260 SC - PTFE single core, robust, chemical resistant and space-saving, for use in machine and plant construction at temperatures: -190°C to +260°C

Info

Excellent chemical, thermal and electrical performance
Space and weight-saving



Good chemical resistance



Flame-retardant



Cold-resistant



Low weight



Oil-resistant



Acid-resistant



Temperature-resistant



UV-resistant

ÖLFLEX® HEAT 260 SC

Benefits

Small outer diameters for maximum saving of space and weight
Resistant to contact with mostly all highly aggressive chemical media
Stress crack resistant to frequent ambient temperature fluctuations

Application range

For use in environments with very high operating temperatures, heavy usage of chemical agents or confined spaces

Typical fields of application

- Aerospace engineering
- High-frequency engineering
- Control cabinets with high heat generation
- Measuring instruments
- Furnaces and brickworks
- Heating equipment and kitchen appliances
- Electric motor building
- Installations in the chemical industry

Product features

Flame-retardant

ÖLFLEX® HEAT 260 made of PTFE

- Outstanding resistance against acids, alkalis, solvents, lacquers, petrol, oils and many other chemical media
- Difficult to inflame
- High dielectric strength and high abrasion resistance
- Low water absorption
- Resistant to microbes
- Adhesion-free insulation materials
- Weather and ozone resistant
- Hydrophobic and dirt-repellent
- High elongation and tear resistance
- Resists contact with liquid nitrogen
- Resistant against hydraulic fluids

Silver plated copper is characterized by good surface conductivity (skin effect) and good solderability

Product Make-up

Silver-plated AWG copper conductor

PTFE core insulation

PTFE = Polytetrafluoroethylene

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000993

ETIM 5.0 Class-Description: Single core cable

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000993

ETIM 6.0 Class-Description: Single core cable

Conductor stranding:

AWG conductor sizes: 7, 19 or 37 wires

Minimum bending radius:

Fixed installation: 4 x outer diameter

Nominal voltage:

U0/U: 300/500 V

Test voltage:

3400 V

Last Update (18.01.2020)

©2020 Lapp Group - Technical changes reserved

ÖLFLEX® HEAT 260 SC

Temperature range:

Fixed installation: -190°C to +260°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Packaging size: Coil 100m

Available as original coil goods only

Also available on large spools and non-returnable drums.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Other colours are available upon request

ÖLFLEX® HEAT 260 SC

Article number	AWG No. and wire number	Outer diameter [mm]	Core colour	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 260 SC					
0094000	28 (7)	0.89	green/yellow	0.9	2
0094001	28 (7)	0.89	black	0.9	2
0094002	28 (7)	0.89	blue	0.9	2
0094003	28 (7)	0.89	brown	0.9	2
0094005	28 (7)	0.89	yellow	0.9	2
0094006	28 (7)	0.89	green	0.9	2
0094007	28 (7)	0.89	violet	0.9	2
0094009	28 (7)	0.89	orange	0.9	2
0094104	28 (7)	0.89	red	0.9	2
0094105	28 (7)	0.89	white	0.9	2
0094106	28 (7)	0.89	grey	0.9	2
0095001	26 (7)	0.99	black	1.4	2.7
0095002	26 (7)	0.99	blue	1.4	2.7
0095006	26 (7)	0.99	green	1.4	2.7
0095007	26 (7)	0.99	violet	1.4	2.7
0095009	26 (7)	0.99	orange	1.4	2.7
0095104	26 (7)	0.99	red	1.4	2.7
0095105	26 (7)	0.99	white	1.4	2.7
0095106	26 (7)	0.99	grey	1.4	2.7
0096000	26 (19)	0.99	green/yellow	1.5	2.9
0096001	26 (19)	0.99	black	1.5	2.9
0096006	26 (19)	0.99	green	1.5	2.9
0106011	26 (19)	0.99	grey	1.5	2.9
0096104	26 (19)	0.99	red	1.5	2.9
0097001	24 (7)	1.12	black	2.2	3.8
0097002	24 (7)	1.12	blue	2.2	3.8
0097003	24 (7)	1.12	brown	2.2	3.8
0097104	24 (7)	1.12	red	2.2	3.8
0097105	24 (7)	1.12	white	2.2	3.8
0098000	24 (19)	1.12	green/yellow	2.3	4
0098001	24 (19)	1.12	black	2.3	4
0098002	24 (19)	1.12	blue	2.3	4
0098003	24 (19)	1.12	brown	2.3	4
0098006	24 (19)	1.12	green	2.3	4

Last Update (18.01.2020)

©2020 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® HEAT 260 SC

Article number	AWG No. and wire number	Outer diameter [mm]	Core colour	Copper index (kg/km)	Weight (kg/km)
0098104	24 (19)	1.12	red	2.3	4
0098105	24 (19)	1.12	white	2.3	4
0098106	24 (19)	1.12	grey	2.3	4
0099001	22 (7)	1.27	black	3.4	5.4
0099002	22 (7)	1.27	blue	3.4	5.4
0099003	22 (7)	1.27	brown	3.4	5.4
0099005	22 (7)	1.27	yellow	3.4	5.4
0099006	22 (7)	1.27	green	3.4	5.4
0099007	22 (7)	1.27	violet	3.4	5.4
0099104	22 (7)	1.27	red	3.4	5.4
0099105	22 (7)	1.27	white	3.4	5.4
0100001	22 (19)	1.27	black	3.7	5.7
0100002	22 (19)	1.27	blue	3.7	5.7
0100003	22 (19)	1.27	brown	3.7	5.7
0100005	22 (19)	1.27	yellow	3.7	5.7
0100009	22 (19)	1.27	orange	3.7	5.7
0100104	22 (19)	1.27	red	3.7	5.7
0100105	22 (19)	1.27	white	3.7	5.7
0101001	20 (7)	1.47	black	5.4	7.7
0101002	20 (7)	1.47	blue	5.4	7.7
0101003	20 (7)	1.47	brown	5.4	7.7
0101006	20 (7)	1.47	green	5.4	7.7
0101104	20 (7)	1.47	red	5.4	7.7
0101105	20 (7)	1.47	white	5.4	7.7
0102001	20 (19)	1.47	black	5.9	8.2
0102002	20 (19)	1.47	blue	5.9	8.2
0102003	20 (19)	1.47	brown	5.9	8.2
0102005	20 (19)	1.47	yellow	5.9	8.2
0102006	20 (19)	1.47	green	5.9	8.2
0102007	20 (19)	1.47	violet	5.9	8.2
0102009	20 (19)	1.47	orange	5.9	8.2
0102104	20 (19)	1.47	red	5.9	8.2
0102105	20 (19)	1.47	white	5.9	8.2
0102106	20 (19)	1.47	grey	5.9	8.2
0103001	18 (7)	1.74	black	8.6	12

Last Update (18.01.2020)

©2020 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® HEAT 260 SC

Article number	AWG No. and wire number	Outer diameter [mm]	Core colour	Copper index (kg/km)	Weight (kg/km)
0102000	20 (19)	1.47	green/yellow	5.9	8.2
0103104	18 (7)	1.74	red	8.6	12
0104000	18 (19)	1.74	green/yellow	9.3	12
0104001	18 (19)	1.74	black	9.3	12
0104002	18 (19)	1.74	blue	9.3	12
0104003	18 (19)	1.74	brown	9.3	12
0104005	18 (19)	1.74	yellow	9.3	12
0104006	18 (19)	1.74	green	9.3	12
0104007	18 (19)	1.74	violet	9.3	12
0104009	18 (19)	1.74	orange	9.3	12
0104104	18 (19)	1.74	red	9.3	12
0104105	18 (19)	1.74	white	9.3	12
0105000	16 (19)	2.04	green/yellow	11.8	16
0105001	16 (19)	2.04	black	11.8	16
0105002	16 (19)	2.04	blue	11.8	16
0105003	16 (19)	2.04	brown	11.8	16
0105005	16 (19)	2.04	yellow	11.8	16
0105006	16 (19)	2.04	green	11.8	16
0105007	16 (19)	2.04	violet	11.8	16
0105009	16 (19)	2.04	orange	11.8	16
0105104	16 (19)	2.04	red	11.8	16
0105105	16 (19)	2.04	white	11.8	16
0106000	14 (19)	2.42	green/yellow	18.7	23
0106001	14 (19)	2.42	black	18.7	23
0106002	14 (19)	2.42	blue	18.7	23
0106003	14 (19)	2.42	brown	18.7	23
0106005	14 (19)	2.42	yellow	18.7	23
0106006	14 (19)	2.42	green	18.7	23
0106104	14 (19)	2.42	red	18.7	23
0106105	14 (19)	2.42	white	18.7	23
0106106	14 (19)	2.42	grey	18.7	23
0107000	12 (19)	2.87	green/yellow	29.6	35
0107001	12 (19)	2.87	black	29.6	35
0107002	12 (19)	2.87	blue	29.6	35
0107003	12 (19)	2.87	brown	29.6	35

Last Update (18.01.2020)

©2020 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® HEAT 260 SC

Article number	AWG No. and wire number	Outer diameter [mm]	Core colour	Copper index (kg/km)	Weight (kg/km)
0107005	12 (19)	2.87	yellow	29.6	35
0107006	12 (19)	2.87	green	29.6	35
0107009	12 (19)	2.87	orange	29.6	35
0107105	12 (19)	2.87	white	29.6	35
0108000	10 (37)	3.4	green/yellow	45.6	51
0108001	10 (37)	3.4	black	45.6	51
0108002	10 (37)	3.4	blue	45.6	51
0108104	10 (37)	3.4	red	45.6	51
0108105	10 (37)	3.4	white	45.6	51

Last Update (18.01.2020)

©2020 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16