



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 8800°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) AVERAGE
BF3380-24B	x = .285 y = .278	1975	790	5 ± 1	28,000 ± 10%	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

	METRIC	DIMENSIONS ARE IN MILLIMETERS				
	THIRD ANGLE PROJECTION	TOLERANCE UNLESS OTHERWISE SPECIFIED				
		1 PL +/- 0	MINIATURE COLD CATHODE FLUORESCENT LAMP			
		2 PL +/- 0	SIZE	FSCM NO.	DRAWING NO.	
		ANGLE +/- 0	A	55335	BF3380-24B	
	DRAWN BY	APPV'D BY	DATE	SCALE	RELEASED DATE	
	L. WENGSTROM	J.K.	8/9/04	NONE	8/9/04	
	RELEASED	8/9/04	- CAD DRAWING -			
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED		REVISION DATE	
					REV. NO.	
					1 OF 1	