

Quality Products. Service Excellence.

Horizontal Ring Cable Manager RB-HRM Series

Features:

- Constructed in 16-gauge steel.
- Flanged at front for added strength.
- Designed to fit standard 19" rails.
- Rings extend 3.69 inches from the panel front.
- Includes four (4) cable pass-through cutouts.
- Designed to mount two (2) units back-to-back.
- Requires mounting hardware.
- Finished in textured RAL9005 black powder paint finish.
- TAA-compliant for GSA Schedule purchases.
- RoHS and REACH compliant.
- Manufactured in North America.

Part of the Rack Basics® line of economy rack solutions.

Accessories

Mounting Hardware

Hook and Loop Roll

	Over	all Dinmens	ions	Usable Mounting Dimensions		
Part No.	Height	Width	Depth	Rack Units	Height	
RB-HRM1	1.72	19.00	3.69	1U	1.75	
RB-HRM2	3.22	19.00	3.69	2U	3.50	

Estimated Cable Fill Capacities

			Recommended Cable Fill (50% Fill			Maximum Cable Fill (100% Fill			
Rack Openir		Opening	Ratio)			Ratio)			
Units	Description	Quantity	Cat 5e	Cat 6	Cat 6a	Cat 5e	Cat 6	Cat 6a	
1U	Channel Opening	1	50	32	22	100	64	45	
	Rear Pass Through	4	16	10	7	32	20	14	
2U	Channel Opening	1	102	65	45	204	130	91	
	Rear Pass Through	4	25	16	11	49	32	22	



Data subject to change without notice



999









© 2023. Hammond Manufacturing Ltd. All rights reserved.