



SS Stainless Steel

**Inch table**

Dimensions in: inches - millimeters

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub> Thread	<sup>3</sup> Length l			d <sub>3</sub>	b	h <sub>1</sub>	h <sub>2</sub>	t min.
1.02 26	10 x 32	.39 10	.63 16	-	.39 10	.43 11	.39 10	.18 4.5	.31 8
1.02 26	1/4 x 20	.63 16	.79 20	.98 25	.39 10	.43 11	.39 10	.18 4.5	.31 8
1.34 34	1/4 x 20	.79 20	.98 25	1.18 30	.47 12	.51 13	.47 12	.20 5	.39 10
1.34 34	5/16 x 18	.63 16	.79 20	1.18 30	.47 12	.51 13	.47 12	.20 5	.39 10

**Metric table**

Dimensions in: millimeters - inches

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub> Thread	<sup>3</sup> Length l			d <sub>3</sub>	b	h <sub>1</sub>	h <sub>2</sub>	t min.
26 1.02	M 4	-	-	-	10 .39	11 .43	10 .39	4.5 .18	7 .28
26 1.02	M 5	10 .39	16 .63	-	10 .39	11 .43	10 .39	4.5 .18	8 .31
26 1.02	M 6	16 .63	20 .79	25 .98	10 .39	11 .43	10 .39	4.5 .18	8 .31
34 1.34	M 6	20 .79	25 .98	30 1.18	12 .47	13 .51	12 .47	5 .20	10 .39
34 1.34	M 8	16 .63	20 .79	30 1.18	12 .47	13 .51	12 .47	5 .20	9 .35

**Specification**

- Stainless steel precision casting  
European Standard No. 1.4308 (AISI CF-8)  
Matte shot-blasted finish

MT

- RoHS compliant

**Information**

Where a greater torque is required GN 434 wing nuts and GN 433 wing screws are a better solution than knurled nuts.

see also...

- Wing Nuts GN 834 (Stainless Steel)
- Wing Screws GN 835 (Stainless Steel)
- Hand Knobs DIN 6335 (Stainless Steel)

How to order (Inch wing nut)	<sup>1</sup> Handle diameter d <sub>1</sub>
<sup>1</sup> <sup>2</sup> <sup>4</sup> GN 434-34-1/4X20-MT	<sup>2</sup> Thread d <sub>2</sub>
	<sup>4</sup> Finish

How to order (Metric wing screw)	<sup>1</sup> Handle diameter d <sub>1</sub>
<sup>1</sup> <sup>2</sup> <sup>3</sup> <sup>4</sup> GN 433-26-M6-16-MT	<sup>2</sup> Thread d <sub>2</sub>
	<sup>3</sup> Length l
	<sup>4</sup> Finish