


VIEW ON MATING SIDE



A = 32 STANDARD CONTACTS L = 3
 C = 32 STANDARD CONTACTS L = 3
 S = 64 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G1/O = CONTACT AREA LEVEL 1 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 2

C	G1/O	c1-32
A	G1/O	σ1-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. J. 2004-XXXX DRAWN: S. 09/09/03 CHECKED: G.L. 09/09/03 APPROVED: L. 09/09/03	QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE	DESIGN UNITS	DIMENSIONS:	THIRD ANGLE PROJECTION	SHT	REV
	MAJOR	4 PLACES ±0. ±.	mm	mm	<input type="checkbox"/> mm <input type="checkbox"/> INCH	<input checked="" type="checkbox"/> INCH ONLY		
	CRITICAL	3 PLACES ±0. ±.	INCH	INCH	<input type="checkbox"/> mm <input checked="" type="checkbox"/> mm ONLY	<input type="checkbox"/> INCH ONLY		REVISE ON CAD ONLY
		2 PLACES ±0. ±.						
REV	DESCRIPTION	DRAWN BY & DATE	TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT		MOLEX INCORPORATED			
		CHECKED BY & DATE	MATERIAL NO. 85003-0282		SHEET NO. 1 OF 1			
		APPROVED BY & DATE	CAD FILENAME SD-85003-0282.S0		DRAWING NO. SD-85003-0282			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						