



Coil Data at 20 °C	Conditions	Min	Typ	Max	Unit
Coil resistance		198	220	242	Ohm
Coil voltage			5		VDC
Rated power			110		mW
Coil current			22		mA
Pull-In voltage				3.75	VDC
Drop-Out voltage		0.5			VDC

Contact Data 85	Conditions	Min	Typ	Max	Unit
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			100	W
Switching voltage	DC or Peak AC			1,000	V
Switching current	DC or Peak AC			1	A
Carry current	DC or Peak AC 100% Duty Cycle			2.5	A
Pulsed carry current	DC or Peak AC 5ms after coil excitation for 50ms max.			3	A
Contact resistance static	Measured with 40% overdrive			150	mOhm
Contact resistance dynamic	Maximum value 1,5 ms after excitation			200	mOhm
Insulation resistance	RH <45 %, 100 V test voltage	10			GOhm
Breakdown voltage		2			kV DC
Operate time incl. bounce	measured with 40% overdrive			1.1	ms
Release time	measured with no coil suppression			0.1	ms
Capacitance	@ 10 kHz across open switch		0.5		pF

Special Product Data	Conditions	Min	Typ	Max	Unit
Dielectric Strength Coil/Contact	according to EN 60255-5	4			kV DC
Housing material			epoxy resin		
Connection pins			FeNi42, tin plated		
Magnetic Shield			Internal Mu Metal Shield		
Reach / RoHS conformity			yes		



Europe: +49 / 7731 8399 0

| Email: info@standexmeder.com

USA: +1 / 508 295 0771

| Email: salesusa@standexmeder.com

Asia: +852 / 2955 1682

| Email: salesasia@standexmeder.com

Item No.:

3305185278

Item:

SHV05-1A85-78L2K

SIL05-1A85-78L2K

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine, duration 11ms, in 3 axis			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature		-40		105	°C
Storage temperature		-40		105	°C
Soldering temperature	wave soldering max. 5 sec.			260	°C
Washability		fully sealed			

General data	Conditions	Min	Typ	Max	Unit
Packaging		Tube per 20 pcs.			

Modifications in the sense of technical progress are reserved

Designed at: 11/24/15 Designed by: THAUKE

Approval at: 11/27/15 Approval by: JHEYDER

Last Change at: Last Change by:

Approval at: Approval by:

Rev. No.: 1