

CMPTA06 NPN  
CMPTA56 PNP

SURFACE MOUNT  
COMPLEMENTARY  
SILICON TRANSISTORS



SOT-23 CASE



www.centrasemi.com

**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CMPTA06 and CMPTA56 are complementary silicon transistors manufactured by the epitaxial planar process, epoxy molded in a surface mount package, designed for small signal general purpose and switching applications.

**MARKING CODES: CMPTA06: C1G  
CMPTA56: C2G**

**MAXIMUM RATINGS:** ( $T_A=25^\circ\text{C}$ )

Collector-Base Voltage  
Collector-Emitter Voltage  
Emitter-Base Voltage  
Continuous Collector Current  
Continuous Base Current  
Peak Base Current  
Power Dissipation  
Operating and Storage Junction Temperature  
Thermal Resistance

**SYMBOL**

$V_{CB0}$  80  
 $V_{CEO}$  80  
 $V_{EBO}$  4.0  
 $I_C$  500  
 $I_B$  100  
 $I_{BM}$  200  
 $P_D$  350  
 $T_J, T_{stg}$  -65 to +175  
 $\theta_{JA}$  429

**UNITS**

V  
V  
V  
mA  
mA  
mA  
mW  
 $^\circ\text{C}$   
 $^\circ\text{C/W}$

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^\circ\text{C}$  unless otherwise noted)

| SYMBOL        | TEST CONDITIONS   | MIN | MAX  | UNITS         |
|---------------|---|-----|------|---------------|
| $I_{CBO}$     | $V_{CB}=80\text{V}$   |     | 100  | nA            |
| $I_{CBO}$     | $V_{CB}=80\text{V}, T_A=150^\circ\text{C}$                        |     | 20   | $\mu\text{A}$ |
| $I_{CEO}$     | $V_{CE}=60\text{V}$   |     | 100  | nA            |
| $BV_{CEO}$    | $I_C=1.0\text{mA}$  | 80  |      | V             |
| $BV_{EBO}$    | $I_E=100\mu\text{A}$  | 4.0 |      | V             |
| $V_{CE(SAT)}$ | $I_C=100\text{mA}, I_B=10\text{mA}$                               |     | 0.25 | V             |
| $V_{BE(ON)}$  | $V_{CE}=1.0\text{V}, I_C=100\text{mA}$                            |     | 1.20 | V             |
| $h_{FE}$      | $V_{CE}=1.0\text{V}, I_C=10\text{mA}$                             | 100 |      |               |
| $h_{FE}$      | $V_{CE}=1.0\text{V}, I_C=100\text{mA}$                            | 100 |      |               |
| $f_T$         | $V_{CE}=2.0\text{V}, I_C=10\text{mA}, f=100\text{MHz}$ (CMPTA06)  | 100 |      | MHz           |
| $f_T$         | $V_{CE}=1.0\text{V}, I_C=100\text{mA}, f=100\text{MHz}$ (CMPTA56) | 50  |      | MHz           |

CMPTA06 NPN  
 CMPTA56 PNP

SURFACE MOUNT  
 COMPLEMENTARY  
 SILICON TRANSISTORS



SOT-23 CASE - MECHANICAL OUTLINE



LEAD CODE:

- 1) Base
- 2) Emitter
- 3) Collector

MARKING CODES:

CMPTA06: C1G  
 CMPTA56: C2G

| DIMENSIONS |        |       |             |      |
|------------|--------|-------|-------------|------|
| SYMBOL     | INCHES |       | MILLIMETERS |      |
|            | MIN    | MAX   | MIN         | MAX  |
| A          | 0.003  | 0.007 | 0.08        | 0.18 |
| B          | 0.006  | -     | 0.15        | -    |
| C          | -      | 0.005 | -           | 0.13 |
| D          | 0.035  | 0.043 | 0.89        | 1.09 |
| E          | 0.110  | 0.120 | 2.80        | 3.05 |
| F          | 0.075  |       | 1.90        |      |
| G          | 0.037  |       | 0.95        |      |
| H          | 0.047  | 0.055 | 1.19        | 1.40 |
| I          | 0.083  | 0.098 | 2.10        | 2.49 |
| J          | 0.014  | 0.020 | 0.35        | 0.50 |

SOT-23 (REV: R3)

R6 (1-February 2010)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)