## SIEMENS

## Data sheet

## 3SU1030-3AB66-0AA0-Z Y12



Twin pushbutton, 22 mm, round, plastic with metal front ring, white, white, Pushbuttons, flat, with laser labeling, lower case

product brand name SIRIUS /	ACT
product designation Twin pus	hbuttons
design of the product Actuating	J/signaling element
product type designation 3SU1	
product line Plastic w	ith metal front ring, matt, 22 mm
Enclosure	
number of command points 1	
Actuator	
design of the actuating element Flat butto	ons
principle of operation of the actuating element momenta	ary contact type
product extension optional	
light source No	
contact module Yes	
color of the actuating element white / w	hite
material of the actuating element plastic	
shape of the actuating element oval	
marking of the actuating element Customiz	zed labeling, text in lower case letters
Front ring	
product component front ring Yes	
design of the front ring Standard	
material of the front ring Metal, m	att
color of the front ring sand gra	у
General technical data	
protection class IP IP66, IP6	37, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3	R, 4, 4X, 12, 13
shock resistance	
according to IEC 60068-2-27 sinusoida	al half-wave 15g / 11 ms
for railway applications according to EN 61373 Category	1, Class B
vibration resistance	
• according to IEC 60068-2-6 10 500	) Hz: 5g
for railway applications according to EN 61373 Category	1, Class B
operating frequency maximum 3 600 1/h	1
mechanical service life (switching cycles) typical 2 000 00	0
reference code according to IEC 81346-2 S	
Substance Prohibitance (Date) 10/01/20	14
Ambient conditions	
ambient temperature	
• during operation -25 +7	
• during storage -40 +8	0°0

environmental category during operation according to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

Installation/ mounting/ dimensions	
height	57.9 mm
width	29.9 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	14.4 mm
installation width	29.9 mm
installation depth	25.7 mm
Certificates/ approvals	

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1030-3AB66-0AA0-Z Y12

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1030-3AB66-0AA0-Z Y12

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1030-3AB66-0AA0-Z Y12

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1030-3AB66-0AA0-Z Y12&lang=en

last modified:

1/26/2022 🖸