

	Hi-Rel Magnetics	Inductance		Test Freq. (kHz)	DC Resistance		Rated DC Current	
		Spec. (uH)	Tol.		Spec. (Ohm)	Tol.	Idc 1 (A)	Idc 2 (A)
5	LGJ7045TS-3R3M2R2-H	3.3uH	+/-20%	100	0.028	+/-20%	2.2	2.3
6	LGJ7045TS-4R7M2R1-H	4.7uH	+/-20%	100	0.031	+/-20%	2.1	2.1
7	LGJ7045TS-6R8M1R9-H	6.8uH	+/-20%	100	0.039	+/-20%	1.9	2.04
8	LGJ7045TS-100M1R8-H	10uH	+/-20%	100	0.047	+/-20%	1.8	1.81
9	LGJ7045TS-150M1R5-H	15uH	+/-20%	100	0.068	+/-20%	1.5	1.46
10	LGJ7045TS-220M1R3-H	22uH	+/-20%	100	0.082	+/-20%	1.3	1.25
11	LGJ7045TS-330M1R1-H	33uH	+/-20%	100	0.12	+/-20%	1.1	1.11
12	LGJ7045TS-470MR90-H	47uH	+/-20%	100	0.18	+/-20%	0.9	0.93
13	LGJ7045TS-680MR75-H	68uH	+/-20%	100	0.27	+/-20%	0.75	0.76
14	LGJ7045TS-101MR60-H	100uH	+/-20%	100	0.39	+/-20%	0.6	0.61
15	LGJ7045TS-151MR50-H	150uH	+/-20%	100	0.55	+/-20%	0.5	0.54
16	LGJ7045TS-221MR40-H	220uH	+/-20%	100	0.83	+/-20%	0.4	0.43
17	LGJ7045TS-331MR35-H	330uH	+/-20%	100	1.15	+/-20%	0.35	0.37
18	LGJ7045TS-471MR31-H	470uH	+/-20%	100	1.80	+/-20%	0.31	0.31

Note) : Idc 1: Depends on the Inductance Saturation. (-10% Saturation from initial L Value)

Idc 2: Depends on the self temperature rise. (+20°C typ.)

Operating temperature: -40°C ~ +125°C (Including self temperature rise)

Storage temperature: -40°C ~ 125°C



\*Recommended Land Pattern (Unit : mm)

