

9 INCHES LENGTH



Connector A
172384
N-Type Jack Straight
Bulkhead - Rear Mount Brass White Bronze + Heatshrink

50 Ohm LMR-195
Continuity/Hi-Pot

Connector B
132454
SMA Jack Straight
Bulkhead - Rear Mount Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.

Connector A		Cable		Connector B	
Part #:	172384	Part #:	LMR-195	Part #:	132454
Description:	N-Type BHD JK Optimized LMR195 50O	Description:	LMR-195 - FEP 0.195	Description:	SMA BHD JK LMR195 Optimized 50O
Type:	N-Type	Dielectric:	FEP	Type:	SMA
Gender:	Jack	Shielding:	Braid	Gender:	Jack
Body Type:	Straight	Diameter:	0.195	Body Type:	Straight
Contact Type:	Crimp	Impedance:	50 Ohm	Contact Type:	Solder
Polarity:	Standard	Sheathing:	None	Polarity:	Standard
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Mounting:	Bulkhead - Rear Mount	Length:	9 Inches	Mounting:	Bulkhead - Rear Mount
Body Material:	Brass			Body Material:	Brass
Body Finish:	White Bronze			Body Finish:	Gold
IP Rating:	None			IP Rating:	None
Contact Material:	Phosphor Bronze			Contact Material:	Beryllium Copper
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	6 GHz			Max. Freq.:	6 GHz
Booting:	N-Type Jack Straight BHD			Booting:	SMA Jack Straight BHD
				Clacking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
N-ST-JK/SMA-ST-JK LMR19 9I

Part No:
Q-23030000D009i

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES