



Wire-end ferrules, Max. wire cross-section: 25 mm², Length: 30 mm, Length of copper pipe: 16 mm, Colour: Yellow

RAL: 1026

Business data

| | |
|--|----------------|
| Article number | 2857.0 |
| Article name | H 25,0/30-D YE |
| GTIN (EAN) | 4044211055820 |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 1.19 g |
| Weight per piece (including packaging) | 1.2 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |
| Product description | Ferrules |
| Colour | Yellow |

Technical data

Dimensions

| | |
|----------------------------------|---------|
| Length | 30 mm |
| Length of copper pipe | 16 mm |
| Diameter of copper pipe | 7.3 mm |
| Diameter plastic collar | 11.2 mm |
| Wall thickness of copper pipe | 0.2 mm |
| Wall thickness of plastic collar | 0.4 mm |

Connection data

| | |
|------------------------------|--------------------|
| Wire cross-section, max. | 25 mm ² |
| Wire cross-section AWG, max. | 4 |
| Stripping length | 18 mm |

Materials

| | |
|---------------------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer |
| Working temperature, min. | -5 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2022-06-10 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Data sheet

2857.0 H 25,0/30-D YE



Approvals

Standards and regulations

DIN 46228-4:1990

yes

Data sheet

2857.0 H 25,0/30-D YE



Media

Data sheet

2857.0 H 25,0/30-D YE



Accessories
