



SCHMATIC
VIEW FROM BASE END
FUSE RECOMMENDED BUT NOT SUPPLIED

| SPECIFICATIONS | | | | | | | | | | | | | | | |
|--|-------|-------|----------|-----------------------|----------|------------------------------------|--|---|---|---------------|--|-------------------|--|----------|--|
| WIRING | INPUT | | OUTPUT | | | | SHAFT ROTATION FOR VOLTAGE INCREASE | TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM BASE END | | | | | | | |
| | VOLTS | HERTZ | VOLTS | CONSTANT CURRENT LOAD | | CONSTANT IMPEDANCE LOAD | | INPUT | OUTPUT | | | | | | |
| | | | | MAX. AMPS | MAX. KVA | MAX. AMPS | | | | MAX. KVA | | | | | |
| SINGLE PHASE | 240 | 50/60 | 0-240 | 10 | 2.40 | 13 | 3.12 | CW | 2-4 | 4-3 | | | | | |
| | | | 0-280 | 10 | 2.80 | — | — | CCW | 2-4 | 2-3 | | | | | |
| | 120 | 50/60 | 0-280 | 10 | 1.20 | — | — | CW | 1-4 | 4-3 | | | | | |
| | | | 0-280 | 10 | 1.20 | — | — | CCW | 2-5 | 2-3 | | | | | |
| UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ± | | | | | | | TITLE: SPECIFICATION CONTROL DRAWING VARIABLE TRANSFORMER TYPE: 2520 C | | | | | | | | |
| FRACTIONS | | | DECIMALS | | | HOLE | | | DRAFT | | | | | | |
| MATERIAL: | | | FINISH: | | | ALL DIMENSIONS APPLY AFTER PLATING | | | STACO ENERGY PRODUCTS CO. DAYTON, OHIO U.S.A. | | | | | | |
| The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein, except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts. | | | | CAT NO | | DRAWN BY | | DATE | | FIRST USED ON | | CUSTOMER APPROVAL | | DATE | |
| | | | | DO NOT SCALE DWG. | | CHECKER | | DATE | | WEIGHT APPROX | | DWG. SIZE | | DWG. NO. | |
| | | | | CODE IDENT NO. 83008 | | ENGINEER | | DATE | | SCALE NONE | | C | | 031-5502 | |