

VAL-SQ SP 120-120/240HLD/FM

This item is no longer available. Should you have any questions, please contact our Sales Team.

Order No.: 2803962



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2803962>

Surge protection device for 120/240 V AC High-Leg Delta configurations. Uses a compact, NEMA rated enclosure that connects easily to an existing enclosure. Hybrid Sine Wave Tracking provides 120 kA surge protection.

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Commercial data

GTIN (EAN)	 4 046356 317085
Note	Made-to-order
sales group	J102
Pack	1 pcs.
Customs tariff	85363030
Catalog page information	Page 71 (TT-2009)

Product description

Surge protection device for 120/240 V AC High-Leg Delta configurations with 120 kA protection

Technical data

Standards

Degree of protection	IP66 / NEMA 4X
Mounting type	3/4 inch NPT male
Design	Parallel MOV

Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	3658 m
Message: Surge protection fault	Phase LEDs
	Audible alarm
	Remote indicator contact
Direction of action	3L-N & N-GND
Width	250.00 mm
Height	122.00 mm
Length	79.00 mm

Protective circuit

IEC category	I + II
Arrester rated voltage U_c	275 V
	150 V
Response time	< 1 ns

Connection, protective circuit

Type of connection	#10 AWG/5.26 mm ² wires (24 in./61 cm long)
Connection method	4-wire + Gnd
Conductor cross section AWG/kcmil min.	10
Conductor cross section AWG/kcmil max	10

Remote indicator contact

Type of connection	#24 AWG/0.205 mm ² wires (24 in./61 cm long)
--------------------	---

Environmental conditions


Standards/regulations	UL 1449 2 nd edition, February 2007
	UL 1283
	IEEE C62.41
	IEEE C62.45

NEMA / UL data

UL type	type 2
Maximum Surge Current per Phase	120 kA
Short-circuit current rating (SCCR)	200 kA
Maximum Circuit Breaker	30 A

Diagrams/Drawings

Circuit diagram



Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;