

- NOTES:
- THE C OPTION SPECIFIES A PIN LENGTH = .20" FOR PANEL LIGHTS MOUNTED IN THE PS40 OR PS44 SOCKET. MOUNTING HARDWARE IS INCLUDED WITH THE SOCKET. DO NOT SELECT THE W OPTION.
  - MODEL 405 HAS NO LENS. OMIT THE LENS DIFFUSION AND COLOR (e.g 405-BG5H-O).
  - $I_v$  = TYPICAL LUMINOUS INTENSITY @  $I_f = 20\text{mA}$  ( $T_a = 25^\circ\text{C}$ ).  $I_v$  IS MEASURED WITHOUT LENS LOW POWER LEDs @  $I_f = 2\text{mA}$ .
  - USE WITH MODEL 405 ONLY.
  - SEE VOLTAGE / CURRENT TABLE FOR DESIGN SPECIFICATIONS. DESIGN CURRENT FOR LOW POWER LEDs = 2mA.
  - $T_a = 25^\circ\text{C}$ . VOLTAGE "2" INDICATES EXTERNAL RESISTOR REQUIRED. VOLTAGES 5H THROUGH 60H ARE VDC. FOR AC OPERATION, INSERT D AFTER VOLTAGE (e.g. 24HD). D INDICATES BUILT-IN RECTIFIER, NOT REQUIRED FOR 5H OR 120VAC. DC OPERATION NOT AVAILABLE FOR 120V. BI-COLOR AND TRI-COLOR NOT AVAILABLE IN AC VOLTAGES.
  - OMIT H WHEN SELECTING A VOLTAGE (e.g 46-RLP-CWO).
  - SELECT -CW OR -NW LENS ONLY. -RAG WIRE LEADS: GREEN ANODE/BLACK CATHODE/RED ANODE. -GAR WIRE LEADS: GREEN CATHODE/BLACK ANODE/RED CATHODE. COMMON LEAD IS THE FIRST LEAD CLOCKWISE FROM REFERENCE MARK ON HEADER. TRI-COLOR 5 OR 12 VOLT, OMIT H IN PART NUMBER.
  - SELECT HIGH INTENSITY LEDS ONLY.
  - OMIT LENS DIFFUSION WHEN SELECTING SMOKED LENS (e.g. 46-NWR-SO).
  - USE APPROPRIATE ESD PRECAUTIONS DURING HANDLING AND OPERATION.
  - MOUNTING HARDWARE PROVIDED
  - THIS DEVICES ARE RoHS COMPLIANT.

REVISIONS					
ECN	REV.	DESCRIPTION	DATE	BY	APPROVED
1126	A	INITIAL RELEASE	1/19/18	AS	OL

### CONFIGURATION FOR MODELS

MODEL	WIRES
$\triangle_C$ C (OPTIONAL)	$\triangle_W$ W (OPTIONAL)

46 W

STANDARD INTENSITY - DIFFUSED ENCAPSULATION		
LED	COLOR	V/C (TABLE)
-BR	RED	I
-BA	AMB	I
-BG	GRN	I
MEDIUM INTENSITY - TINTED ENCAPSULATION		
LED	COLOR	V/C (TABLE)
-BCR	RED	I
-BCA	AMB	I
-BCG	GRN	I
HIGH INTENSITY - WATERCLEAR ENCAPSULATION		
LED	COLOR	V/C (TABLE)
-NWR	RED	I
-NWO	ORG	I
-NWA	AMB	I
-NWG	GRN	II
-NWB	BLU	II
-NWW	CWHT	II
-NWL	WWHT	II
-NKR	RED	I
-NKO	ORG	I
-NKA	AMB	I
-NKG	GRN	II
-NKB	BLU	II
-NKW	CWHT	II
-NKL	WWHT	II

WIRE LENGTH (OPTIONAL)*	
NUMBER	LENGTH (in)
8	8"
12	12"
16	16"
18	18"
24	24"
36	36"
40	40"
60	60"

VOLTAGE
2
5H
12H
15H
24H
28H
48H
60H
120 $\triangle_9$

LENS DIFFUSION
-C (CLEAR)
-N (DIFFUSED)


LENS COLOR
R (RED)
A (AMBER)
Y (YELLOW)
G (GREEN)
B (BLUE)
W (WATER CLEAR)
-S (SMOKE) $\triangle_{10}$

BEZEL COLOR
O (BLACK)
9 (WHITE)

#### \*STANDARD WIRE LENGTH:

IF THE CONFIGURATION DOES NOT INCLUDE A NUMBER AFTER THE "W" USE THIS STANDARD:  
 6.0" +1.0" -0" TOTAL LENGTH (NOMINAL)/.50" STRIPPED +1/8" -0", RED ANODE/ BLACK CATHODE, 24 AWG TPB UL1061 INSULATION.

SPECIALITY LEDs - DIFFUSED ENCAPSULATION			
LED	COLOR	DESCRIPTION	V/C (TABLE)
$\triangle_5$ -RLP	RED	LOW POWER	NOTE 5
$\triangle_7$ -ALP	AMB	LOW POWER	NOTE 5
$\triangle_7$ -GLP	GRN	LOW POWER	NOTE 5
$\triangle_8$ -LRG	RED/GRN	BI-COLOR, RED CATHODE	I
$\triangle_8$ -RAG	RED/AMB/GRN	TRI-COLOR, COMMON CATHODE	I
$\triangle_8$ -GAR	GRN/AMB/RED	TRI-COLOR, COMMON ANODE	I



ISOMETRIC VIEW ONLY FOR REF.

VOLTAGE/CURRENT	
DESIGN $V_f/I_f$	MAX $V_f/I_f$
<b>V/C Table I</b>	
5V/22mA	5.5v/28mA
12V/20mA	14V/25mA
15V/24mA	16.5V/28mA
24V/17mA	26V/20mA
28V/16.5mA	30V/18mA
48V/15mA	50V/16mA
60V/9mA	65V/10mA
120VAC/3.5mA	130VAC/4mA

VOLTAGE / CURRENT	
DESIGN $V_f/I_f$	MAX $V_f/I_f$
<b>V/C Table II</b>	
5V/15mA	5.5v/23mA
12V/15mA	14V/20mA
15V/15mA	16.5V/18mA
24V/15mA	26V/18mA
28V/15mA	30V/17mA
48V/9.5mA	50V/10mA
60V/7mA	65V/8mA
120VAC/3.5mA	130VAC/4mA

The information in this document is the exclusive **PROPRIETARY** property of **VISUAL COMMUNICATIONS COMPANY, LLC**. It is disclosed with the understanding that acceptance or review by the recipient constitutes an undertaking by the recipient: (1) to hold this information in strict confidence (2) not to disclose, duplicate, copy, or use the information, in whole or in part, for any purpose other than that for which disclosed

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES (MM) SHOWN FOR REFERENCE ALL ANGLES ARE IN DEGREES		MATERIAL N/A		 12780 DANIELSON CT, SUITE A, POWAY, CA 92064 PHONE: (800)522-5546 • WWW.VCC-LITE.COM	
GENERAL TOLERANCES		FINISH N/A			
.XX ± 0.025	.X ± 0.63	DRW	A.SANCHEZ	12/19/17	DESC <b>.250" PANEL MOUNT REFLECTOR</b>
.XXX ± 0.010	.XX ± 0.25	D-ENG	A.SANCHEZ	12/19/17	PART NO SEE TABLES
BREAK ALL CORNERS AND SHARP EDGES .030 MAX		P-ENG	O.LARA / G.RUIZ	1/17/18	SIZE <b>B</b>
DIMENSIONS INSPECTION CRITICAL ANGLE ± 1°		QC	E.LARA	1/19/18	DRW NO <b>46 SERIES</b>
THIRD ANGLE PROJECTION		DO NOT SCALE DRAWING PRINTED COPIES ARE UNCONTROLLED		SCALE: 1:1	REV <b>A</b>
				SHEET: 1 OF 1	