



| Date    | SYM | REVISION RECORD             | AUTH | DR.  | CK. |
|---------|-----|-----------------------------|------|------|-----|
| 2/25/06 | A   | ADDED "ROHS COMPLIANT"      | T.B. | B.S. |     |
| 5/02/08 | B   | ADDED NOTE                  | T.B. | B.S. |     |
| 7/11/14 | C   | UPDATED TO ROHS 2 COMPLIANT | T.B. | B.S. |     |
|         |     |                             |      |      |     |
|         |     |                             |      |      |     |

NOTE:  
 ORIENTATION OF SNAPS AND WIRES VARIES  
 AND IS SHOWN FOR REFERENCE ONLY.  
 RED WIRE TO POSITIVE CONTACT.  
 BLACK WIRE TO NEGATIVE CONTACT.

ROHS 2 COMPLIANT

| N0. | PART NAME     | MATERIAL   | QTY. | Tolerance<br>(Except as noted) | MPD Memory Protection Devices, Inc<br>200 Broad Hollow Road, Farmingdale, New York 11735 |                      |  |
|-----|---------------|--|------|--------------------------------|--|----------------------|--|
| 1   | COVER         | PVC COVER OVER FIBERBOARD                        | 1    | decimal<br>±.5 (.020)          | Scale  | Drawn By B.S.        |  |
| 2   | BLACK WIRE(-) | 24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C | 1    |                                |  | Approved By T.B.     |  |
| 3   | RED WIRE (+)  | 24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C | 1    | Fractional<br>± .8 (.030)      | Title 9 VOLT BATTERY SNAP-I STYLE-12" WIRE LEADS   |                      |  |
| 4   | FEMALE SNAP   | BRASS, NICKLE PLATED                             | 1    |                                | Date 7/11/14   | Drawing Number BS12I |  |
| 5   | MALE SNAP     | BRASS NICKLE PLATED                              | 1    |                                | Angular<br>± 3°  |                      |  |