

[Skip to content](#)



Our commitment. Your advantage.



• [Products](#)

- [By Type](#)
 - [Connectors](#)
 - [Electromechanical Components](#)
 - [Electronic Modules](#)
 - [Fiber Optics](#)
 - [Filters](#)
 - [Identification & Labeling](#)
 - [Passive Components](#)
 - [Power Sources](#)
 - [RF & Microwave Products](#)
 - [Tooling Products](#)
 - [Touch Screen Displays](#)
 - [Tubing, Molded and Harnessing Products](#)
 - [Wire, Cable and Cable Assemblies](#)
 - [List all product types...](#)
- [By Industry](#)
 - [Aerospace & Defense Products](#)
 - [Appliance](#)
 - [Automotive](#)
 - [Communications](#)
 - [Computer & Consumer Electronics](#)
 - [Industrial & Commercial](#)
 - [Instrumentation & Medical](#)
- [By Brand](#)
- [A to Z](#)
- [Product News](#)

• [Documentation](#)

- [Find Documents & Drawings](#)
- [Find CAD Models](#)
- [SPICE/Electrical Models](#)
- [NAFTA Certificate of Origin](#)
- [White Papers](#)

• [Resources](#)

- [RoHS Compliance & Alternates](#)
- [Cross Reference Products](#)
- [Compare Multiple Products](#)
- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

• [My Account](#)

- [Sign In](#)
- [Register](#)

• [Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

CNT-35-96 Product Details



CNT-35-96



Active

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- CNT Series
- Time Delay Relay
- Input Voltage = 24 - 240 VAC
- Input Voltage = 24 - 240 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O

[View all Features](#) | [Find Similar Products](#)

[Previous](#) [1](#) ... [16](#) [[17](#)] [18](#) [19](#) [20](#) [Next](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [CNT Multifunction, Digital Time Delay Relay/Counter](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Time Delay Relay
- Termination Type = 11-Pin Octal Style Plug

Electrical Characteristics:

- Input Voltage (VAC) = 24 240
- Input Voltage (VDC) = 24 240
- Contact Rating = 10A @ 30 VDC or 277 VAC

Body Related Features:

- [Series](#) = CNT

Contact Related Features:

- Mounting Options = Socket
- Mode of Operation = Programmable - 10 Timing Functions
- Delay Time = 0.1 seconds to 9990 hours
- Type of Control = Thumbwheel Switches
- Repeatability, Max. = 0.1% 0.05 seconds
- Approved Standards = CSA Certified, UL Recognized
- Contact Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 47.80 x 47.80 x 71.90 [1.883 x 1.883 x 2.832]
- Enclosure = Beige Plastic 1/16 DIN Case

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process

Conditions for Usage:

- Temperature Range (C) = -10 +55

Other:

- Brand = Potter & Brumfield