



JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF22180-28B	x = .346 y = .319	1140 @ 0°C	380	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
			TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
B RATED LIFE HRS MINIMUM 7/30/09 A CIRCUIT & LAMP VOLTAGE CHANGE 7/19/04 RELEASED & CANCEL P-0303-14 9/2/03			DRAWN BY L. WENGSTROM APPVD BY L.R. DATE 7/30/09		SIZE A FSCM NO. 55335		DRAWING NO. BF22180-28B	
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE RELEASED DATE 9/2/03		REVISION DATE 7/30/09 REV. NO. B SHEET 1 OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JKL Components:](#)

[BF22180-28B](#)