



**ISO 9001:2000**

## Plunger Clips

### Plunger Clip

---



Model # BU-00201-\*/BU-00202-\*/BU-00203-\*

- Material: Cap & Body: glass filled nylon; Spring: stainless steel; Contact: beryllium copper; insulated to a single contact point
- Length: 1.75" (44mm) (BU-00201-\*); 2.50" (63mm) (BU-00202-\*); 3.50" (88mm) (BU-00203-\*)
- \*Std. Colors: -0 Black, -2 Red
- Rating: 1000 Volts, 10 Amps

### Safety Plunger Clip Adapter

---



Model # BU-00207-\*

- Material: Cap & Body: nylon; Spring: stainless steel; Contact: beryllium copper
- Length: 2.23" (56.64mm)
- \*Std. Colors: -0 Black, -2 Red
- Rating: 1000 Volts, 15 Amps

### Mini-Micro Plunger Clip

---



Model # BU-00208-\*

- Material: Cap & Body: tough, durable nylon; Spring: stainless steel compression coil; Contact: gold-plated beryllium copper
- Length: 1.75" (44mm)
- \*Std Colors: -0 Black, -2 Red
- Rating: 600 Volts, 3 Amps

### Right Angle Insulated Plunger Hook Clip

---



Model # BU-20431-\*

- Compatible with all shrouded, unshrouded, or retractable 0.16" (4mm) banana plugs
- Material: Housing: nylon. Contact: nickel-plated beryllium copper
- Length: 4.60" (116.84mm); the hook extends 0.41" (10mm) when fully depressed
- \*Std Colors: -0 Black, -2 Red, -4 Yellow, -6 Blue
- Rating: 1000V, 15 Amps, IEC 1010 Compliant

### Right Angle Insulated Plunger Clamp Clip

---



Model # BU-20432-\*/BU-20433-\*

- Compatible with all shrouded, unshrouded, or retractable 0.16" (4mm) banana plugs
- Material: Housing: nylon. Contact: nickel-plated beryllium copper
- Length: 5.50" (139.7mm) (BU-20432-\*); 7.50" (190.5mm) (BU-20433-\*)
- \*Std Colors: -0 Black, -2 Red, -4 Yellow, -6 Blue
- Rating: 1000V, 1 Amps, IEC 1010 Compliant

## Right Angle Insulated Plunger Jaw Clip

---



Model # BU-20434-\*

- Compatible with all shrouded, unshrouded, or retractable 0.16" (4mm) banana plugs
- Material: Housing: nylon. Contact: nickel-plated steel
- Length: 5.26" (133.6mm); the steel jaws extend 0.48" (12mm) and open to 1" (25mm)
- \*Std Colors: -0 Black, -2 Red, -4 Yellow, -6 Blue
- Rating: 1000V, 15 Amps, IEC 1010 Compliant