



Materials and Finish

Housing:
Polycarbonate, UL 94V-2 rated

Contact Material:
High Strength Copper Alloy
JIS C5191R-H

Contact Plating:
1000 Series:
Gold Flash over 100u" Nickel

Electrical Characteristics

Insulation Resistance:
500 Megohms Min.

Dielectric Withstanding Voltage:
1000 VAC RMS, 60Hz
for 1 minute

Contact Resistance:
20 milliohms Max.

Current Rating:
1.5 amps

Recommended Wire Gauge:
26-28 AWG

Operating Temp:
-55°C to +85°C

Part Number	Contact Area Plating Finish
MP1010RX-1000K	Gold Flash (1000 option)
MP1010RX-5000K	50u" Gold (5000 option)



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	10/18/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	9/19/05
A1	03/25/11	Remove Prelim	S. Vien	H. MA		

MP1010RX-1000K
x = plating option (1 or 5)

Modular Plug for Stranded Wire, Keyed, RoHS Compliant
10 position, 10 contact, Gold Flash

