

tesa® 4334 Precision Mask®

High grade paper masking tape for precise and flat paint edges

PRODUCT INFORMATION

Product Description

tesa® 4334 Precision Mask® consists of an extra-thin and strong paper backing coated with an acrylic adhesive.

The combination of the highly equipped backing material and the outstanding special adhesive formulation allows easy removability up to 5 months after application, with 4 weeks of UV resistance. This enables multiple working processes in only one covering process.

Main Application

This tape is suited for almost all indoor paint works.

tesa® 4334 Precision Mask® is applicable with water-based paints and lacquers and fits even for high-class spatula techniques.

It is suitable for a variety of common surfaces such as glass, aluminium, hard-PVC and wood.

It is especially suited for indoor applications when a precise razor-sharp paint edge is needed.

Technical Data

■ Backing material	flat paper	■ Adhesion to steel	1.85 N/cm
■ Total thickness	90 µm	■ Elongation at break	4 %
■ Type of adhesive	acrylic	■ Tensile strength	30 N/cm

Properties

■ Hand tearability	++	■ Suitable for rough surfaces	+
■ Conformability	++	■ Paint anchorage	++
■ Suitable for sensitive surfaces	+	■ Sharp colour edge	++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04334>

Page 1 of 1 / As of 10/01/15