

**USB** 





✓ Active



PRODUCT DRAWING



3D PDF

## TE CONNECTIVITY (TE)

## USB CONN R/A SMT REC ASS'Y 4P

Universal Serial Bus | A

1-5353583-4

TE Internal Number: 1-5353583-4

Always EU RoHS/ELV Compliant

Size Standard

Connector Style Receptacle

Number of Positions 4

Number of Ports 1

Orientation Right Angle

**Product Drawings** 

RECEPTACLE ASS'Y R/A SMT STANDARD TYPE USB CONNECTOR

PDF **English** 

CAD Files

3D PDF

PDF 3D

Customer View Model

2D\_DXF.ZIP English

Customer View Model

3D\_IGS.ZIP English

Customer View Model

3D\_STP.ZIP English

3D PDF PDF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

**Product Type Features** 

Size

Standard

Connector Style

Receptacle

Orientation

Right Angle

LED

Without

Product Type

Connector

Applies To

Printed Circuit Board

Configuration Features	Number of Positions	4
	Number of Ports	1
	Panel Ground	With
	Panel Ground Location	Right/Left
	Panel Ground Type	M2 Threaded Hole
Body Features	Shell Plating Material	Tin
	Shell Plating Finish	Bright
Contact Features	Contact Mating Area Plating Thickness	.76 μm [ 29.92 μin ]
	Contact Mating Area Plating Material	Gold or Gold Flash over Palladium Nickel
Termination Features	Termination Method	Solder
	Contact Termination Type	Surface Mount
Mechanical Attachment	Mounting Location	Тор
	Locking Feature	Without
	Locating Posts	With
	PCB Mount Retention Type	SMT Hold-Down
Housing Features	Housing Material	Thermoplastic
	Housing Color	Black
Dimensions	PCB Thickness (Recommended)	1 mm [ .039 in ]
Operation/Application	Pick and Place	Pick and Place Cover
	Industrial USB Connector	No
Industry Standards	Industry Standard	USB 2.0
0.1.5.5.	D. L. C. M. C. L.	/5
Packaging Features	Packaging Method	Tape, Tray/Box
	Packaging Quantity	55
Product Compliance		

Product Compliance

Statement of Compliance PDF

VIEW ALL PRODUCT COMPLIANCE