

Multilayer Ceramic Chip Capacitors

General use(Low profile)

CGB series

Type: **CGB2(C1005[EIA CC0402])**
 CGB3(C1608[EIA CC0603])
 CGB4(C2012[EIA CC0805])

Issue date: August 2011

- All specifications are subject to change without notice.
 - Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.
-

REMINDERS

Please read this before using the product.

SAFETY REMINDERS

REMINDERS

1. If you intend to use a product listed in this catalog for a purpose that may cause loss of life or other damage, you must contact our company's sales window.
2. We may modify products or discontinue production of a product listed in this catalog without prior notification.
3. We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
4. If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
5. Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
6. We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
7. This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.
8. The descriptions in this catalog apply as of August, 2011.

Multilayer Ceramic Chip Capacitors

General Use(Low Profile)

Conformity to RoHS Directive

CGB Series


FEATURES

- Suitable for applications with height restrictions due to their low-profile design.

APPLICATION EXAMPLES

- Applications with height restrictions, such as cellular phones, smartphones, LCD modules.

SHAPES AND DIMENSIONS



DIMENSIONS

The dimensions of each product are described within the product name.

Dimensions L×W

The fourth digit number in the product name corresponds to the dimensions of L×W.

Refer to the table below for specific values.

Dimension code	Dimensions in mm		
	L	W	B
2	1.0±0.05	0.5±0.05	0.1min.
3	1.6±0.1	0.8±0.1	0.2min.
4	2.0±0.2	1.25±0.2	0.2min.

- Dimension tolerances are typical values.

Product's Thickness T

The value in parentheses at the end of the product name corresponds to thickness T.

Refer to the table of "CAPACITANCE RANGES" for specific values.

- For more information about the products of other capacitance or data, please contact us.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

- All specifications are subject to change without notice.
- Please read the precautions before using this catalog.

PRODUCT IDENTIFICATION

CGB 3 B 1 X5R 1C 225 K (055 A C)
 (1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11)

(1) Series name
(2) Dimensions L×W

2	1.0×0.5mm
3	1.6×0.8mm
4	2.0×1.25mm

(3) Dimensions T

A	0.33mm (max.)
B	0.55mm (max.)

- Overlaps with (9).

**(4) Test voltage of the high temperature load test
(guaranteed voltage)**

1	1× the rated voltage
2	2× the rated voltage
3	1.5× the rated voltage
4	1.2× the rated voltage
5	1.1× the rated voltage

(5) Capacitance temperature characteristics
Class 2 (Temperature stable and general purpose)

Temperature characteristics	Capacitance change	Temperature range
X5R	±15%	-55 to +85°C
X6S	±22%	-55 to +105°C
JB	±10%	-25 to +85°C

(6) Rated voltage E_{dc}

0G	4V
0J	6.3V
1A	10V
1C	16V
1E	25V

(7) Nominal capacitance

The capacitance is expressed in three digit codes and in units of pico farads (pF).

The first and second digits identify the first and second significant figures of the capacitance.

The third digit identifies the multiplier.

R designates a decimal point.

474	470,000pF
225	2,200,000pF (2.2μF)

(8) Capacitance tolerance

Symbol	Tolerance	Applicable capacitance range
K	±10%	Over 10pF
M	±20%	

(9) Dimensions T

Expressed by a three-digit number in mm units.

The second and third digits denote the first and second decimal places, respectively.

033	0.33mm (max.)
055	0.55mm (max.)

- Overlaps with (3).

(10) Packaging style

A	ø178mm reel with 4mm-pitch
B	ø178mm reel with 2mm-pitch
C	ø178mm reel with 1mm-pitch
D	ø330mm reel with 4mm-pitch
E	ø330mm reel with 2mm-pitch
F	ø330mm reel with 1mm-pitch
H	Bulk(bag)
J	ø330mm reel with 8mm-pitch
K	ø178mm reel with 8mm-pitch

(11) TDK internal code

In brochures issued in August, 2011 and later, the product thickness and packing specifications are described at the end of the ordering name [the product name described in brochures] in parentheses.

Since the existing ordering name could not clearly express the product thickness and packing specifications, it has been changed to a new product description method that solves this inconvenience.

Please be aware that the last five digits of the ordering name on the delivery label and those in the brochure differ.

No changes have been made to the delivery name.

(Example)

Brochure issued date	Ordering name (description in the brochure)	Delivery name (description on the delivery label)
Prior to July, 2011	C1608X5R1C105K	C1608X5R1C105KT000N
August, 2011 or later	C1608X5R1C105K(080AA)	C1608X5R1C105KT000N

- For more information about the products of other capacitance or data, please contact us.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

- All specifications are subject to change without notice.

Please read the precautions before using this catalog.

CAPACITANCE RANGES: CLASS 2
TEMPERATURE CHARACTERISTICS: X5R(±15%)

Capacitance	Dimension L×W	Thickness T(mm)	Capacitance tolerance	Part No.	
				Rated voltage Edc: 25V	Rated voltage Edc: 16V
330nF	1005	0.33max.	±10%	CGB2A1X5R1C334K(033BC)	
			±20%	CGB2A1X5R1C334M(033BC)	
470nF	1005	0.33max.	±10%	CGB2A1X5R1C474K(033BC)	
			±20%	CGB2A1X5R1C474M(033BC)	
	1608	0.55max.	±10%	CGB3B1X5R1E474K(055AC)	
			±20%	CGB3B1X5R1E474M(055AC)	
1μF	1608	0.55max.	±10%	CGB3B1X5R1C105K(055AC)	
			±20%	CGB3B1X5R1C105M(055AC)	
1.5μF	2012	0.55max.	±10%	CGB4B1X5R1E105K(055AC)	
			±20%	CGB4B1X5R1E105M(055AC)	
1.5μF	1608	0.55max.	±10%	CGB3B1X5R1C155K(055AC)	
			±20%	CGB3B1X5R1C155M(055AC)	
2.2μF	1608	0.55max.	±10%	CGB3B1X5R1C225K(055AC)	
			±20%	CGB3B1X5R1C225M(055AC)	
	2012	0.55max.	±10%	CGB4B1X5R1C225K(055AC)	
			±20%	CGB4B1X5R1C225M(055AC)	

TEMPERATURE CHARACTERISTICS: X5R(±15%)

Capacitance	Dimension L×W	Thickness T(mm)	Capacitance tolerance	Part No.		
				Rated voltage Edc: 10V	Rated voltage Edc: 6.3V	Rated voltage Edc: 4V
330nF	1005	0.33max.	±10%	CGB2A3X5R1A334K(033BB)		
			±20%	CGB2A3X5R1A334M(033BB)		
470nF	1005	0.33max.	±10%	CGB2A3X5R1A474K(033BB)		
			±20%	CGB2A3X5R1A474M(033BB)		
680nF	1005	0.33max.	±10%	CGB2A1X5R1A684K(033BC)		
			±20%	CGB2A1X5R1A684M(033BC)		
	0.33max.	±10%	CGB2A3X5R0J684K(033BB)			
			±20%	CGB2A3X5R0J684M(033BB)		
1μF	1005	0.33max.	±10%	CGB2A1X5R1A105K(033BC)		
			±20%	CGB2A1X5R1A105M(033BC)		
1.5μF	1608	0.55max.	±10%	CGB2A3X5R0J105K(033BB)		
			±20%	CGB2A3X5R0J105M(033BB)		
2.2μF	1608	0.55max.	±10%	CGB3B3X5R1A155K(055AB)		
			±20%	CGB3B3X5R1A155M(055AB)		
	2012	0.55max.	±10%	CGB3B3X5R1A225K(055AB)		
			±20%	CGB3B3X5R1A225M(055AB)		
3.3μF	1608	0.55max.	±10%	CGB4B1X5R1A225K(055AC)		
			±20%	CGB4B1X5R1A225M(055AC)		
	0.55max.	±10%	CGB3B1X5R1A335K(055AC)			
			±20%	CGB3B1X5R1A335M(055AC)		
2012	0.55max.	±10%	CGB3B3X5R0J335K(055AB)			
		±20%	CGB3B3X5R0J335M(055AB)			
4.7μF	1608	0.55max.	±10%	CGB4B1X5R1A335K(055AC)		
			±20%	CGB4B1X5R1A335M(055AC)		
	0.55max.	±10%	CGB3B1X5R1A475K(055AC)			
			±20%	CGB3B1X5R1A475M(055AC)		
2012	0.55max.	±10%	CGB3B3X5R0J475K(055AB)			
		±20%	CGB3B3X5R0J475M(055AB)			
0.55max.	±10%	CGB4B1X5R0J475K(055AC)				
		±20%	CGB4B1X5R0J475M(055AC)			

- For more information about the products of other capacitance or data, please contact us.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

Please read the precautions before using this catalog.

CAPACITANCE RANGES: CLASS 2
TEMPERATURE CHARACTERISTICS: X6S(±22%)

Capacitance	Dimension L×W	Thickness T(mm)	Capacitance tolerance	Part No.		
				Rated voltage Edc: 10V	Rated voltage Edc: 6.3V	Rated voltage Edc: 4V
330nF	1005	0.33max.	±10%	CGB2A1X6S1A334K(033BC)		
			±20%	CGB2A1X6S1A334M(033BC)		
		0.33max.	±10%	CGB2A3X6S0J334K(033BB)		CGB2A3X6S0J334M(033BB)
			±20%	CGB2A3X6S0J334M(033BB)		
470nF	1005	0.33max.	±10%	CGB2A1X6S1A474K(033BC)		
			±20%	CGB2A1X6S1A474M(033BC)		
		0.33max.	±10%	CGB2A3X6S0J474K(033BB)		CGB2A3X6S0J474M(033BB)
			±20%	CGB2A3X6S0J474M(033BB)		
680nF	1005	0.33max.	±10%	CGB2A1X6S0G684K(033BC)		
			±20%	CGB2A1X6S0G684M(033BC)		
1μF	1005	0.33max.	±10%	CGB2A1X6S0G105K(033BC)		
			±20%	CGB2A1X6S0G105M(033BC)		
1.5μF	1608	0.55max.	±10%	CGB3B1X6S1A155K(055AC)		
			±20%	CGB3B1X6S1A155M(055AC)		
		0.55max.	±10%	CGB3B3X6S0J155K(055AB)		CGB3B3X6S0J155M(055AB)
			±20%	CGB3B3X6S0J155M(055AB)		
2.2μF	1608	0.55max.	±10%	CGB3B1X6S1A225K(055AC)		
			±20%	CGB3B1X6S1A225M(055AC)		
		0.55max.	±10%	CGB3B3X6S0J225K(055AB)		CGB3B3X6S0J225M(055AB)
			±20%	CGB3B3X6S0J225M(055AB)		
3.3μF	1608	0.55max.	±10%	CGB3B1X6S0G335K(055AC)		
			±20%	CGB3B1X6S0G335M(055AC)		
4.7μF	1608	0.55max.	±10%	CGB3B1X6S0G475K(055AC)		
			±20%	CGB3B1X6S0G475M(055AC)		

- For more information about the products of other capacitance or data, please contact us.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

Please read the precautions before using this catalog.

CAPACITANCE RANGES: CLASS 2
TEMPERATURE CHARACTERISTICS: JB(±10%)

Capacitance	Dimension L×W	Thickness T(mm)	Capacitance tolerance	Part No.	
				Rated voltage Edc: 25V	Rated voltage Edc: 16V
330nF	1005	0.33max.	±10%	CGB2A1JB1C334K(033BC)	
			±20%	CGB2A1JB1C334M(033BC)	
470nF	1005	0.33max.	±10%	CGB2A1JB1C474K(033BC)	
			±20%	CGB2A1JB1C474M(033BC)	
	1608	0.55max.	±10%	CGB3B1JB1E474K(055AC)	
			±20%	CGB3B1JB1E474M(055AC)	
1μF	1608	0.55max.	±10%	CGB3B1JB1C105K(055AC)	
			±20%	CGB3B1JB1C105M(055AC)	
1.5μF	2012	0.55max.	±10%	CGB4B1JB1E105K(055AC)	
			±20%	CGB4B1JB1E105M(055AC)	
1.5μF	1608	0.55max.	±10%	CGB3B1JB1C155K(055AC)	
			±20%	CGB3B1JB1C155M(055AC)	
2.2μF	1608	0.55max.	±10%	CGB3B1JB1C225K(055AC)	
			±20%	CGB3B1JB1C225M(055AC)	
	2012	0.55max.	±10%	CGB4B1JB1C225K(055AC)	
			±20%	CGB4B1JB1C225M(055AC)	

TEMPERATURE CHARACTERISTICS: JB(±10%)

Capacitance	Dimension L×W	Thickness T(mm)	Capacitance tolerance	Part No.		
				Rated voltage Edc: 10V	Rated voltage Edc: 6.3V	Rated voltage Edc: 4V
330nF	1005	0.33max.	±10%	CGB2A3JB1A334K(033BB)		
			±20%	CGB2A3JB1A334M(033BB)		
470nF	1005	0.33max.	±10%	CGB2A3JB1A474K(033BB)		
			±20%	CGB2A3JB1A474M(033BB)		
680nF	1005	0.33max.	±10%	CGB2A1JB1A684K(033BC)		
			±20%	CGB2A1JB1A684M(033BC)		
	0.33max.	±10%	CGB2A3JB0J684K(033BB)			
			±20%	CGB2A3JB0J684M(033BB)		
1μF	1005	0.33max.	±10%	CGB2A1JB1A105K(033BC)		
			±20%	CGB2A1JB1A105M(033BC)		
1.5μF	1608	0.55max.	±10%	CGB2A3JB0J105K(033BB)		
			±20%	CGB2A3JB0J105M(033BB)		
1.5μF	1608	0.55max.	±10%	CGB3B3JB1A155K(055AB)		
			±20%	CGB3B3JB1A155M(055AB)		
	1608	0.55max.	±10%	CGB3B3JB1A225K(055AB)		
			±20%	CGB3B3JB1A225M(055AB)		
2.2μF	2012	0.55max.	±10%	CGB4B1JB1A225K(055AC)		
			±20%	CGB4B1JB1A225M(055AC)		
	1608	0.55max.	±10%	CGB3B1JB1A335K(055AC)		
			±20%	CGB3B1JB1A335M(055AC)		
3.3μF	1608	0.55max.	±10%	CGB3B3JB0J335K(055AB)		
			±20%	CGB3B3JB0J335M(055AB)		
3.3μF	2012	0.55max.	±10%	CGB4B1JB1A335K(055AC)		
			±20%	CGB4B1JB1A335M(055AC)		
	1608	0.55max.	±10%	CGB3B1JB1A475K(055AC)		
			±20%	CGB3B1JB1A475M(055AC)		
4.7μF	1608	0.55max.	±10%	CGB3B3JB0J475K(055AB)		
			±20%	CGB3B3JB0J475M(055AB)		
	2012	0.55max.	±10%	CGB4B1JB0J475K(055AC)		
			±20%	CGB4B1JB0J475M(055AC)		

- For more information about the products of other capacitance or data, please contact us.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

Please read the precautions before using this catalog.