

## Printed-circuit board connector - CCA 2,5/14-G P20 THR - 1836463

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Header, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 14, pitch: 5 mm, Color: black, contact surface: Tin, mounting: THR soldering, User information and design recommendations for through hole reflow technology can be found under "Downloads"



The figure shows a 16-position version

#### Why buy this product

- ☑ Designed for integration into the SMT soldering process
- Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- ☑ Closed contour for optimum stability of the plug-in connection













### **Key Commercial Data**

Packing unit	1 STK
Minimum order quantity	50 STK
GTIN	4 055626 020761
GTIN	4055626020761
Custom tariff number	85366930
Country of origin	Germany

### Technical data

#### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



## Printed-circuit board connector - CCA 2,5/14-G P20 THR - 1836463

### Classifications

#### eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

#### **ETIM**

ETIM 5.0	EC002637
ETIM 6.0	EC002637

#### **UNSPSC**

UNSPSC 13.2	39121409

#### Accessories

#### Accessories

#### Coding element

Coding star - CR-MSTB - 1734401



Coding section, inserted into the recess in the header or the inverted plug, red insulating material

### Coding section - CR-MSTB NAT HT - 1954362



HT coding section, prior to the reflow soldering process it is inserted into the recess on the header, made from high-temperature-resistant beige insulation material

#### Marker pen

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm



# Printed-circuit board connector - CCA 2,5/14-G P20 THR - 1836463

## Accessories

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1836463