




Technical data

7322

Single row or matched pairs of angular contact ball bearings

VISUAL (S)



7322

Single row or matched pairs of angular contact ball bearings

PRODUCT DEFINITION

Brand	NTN
d - Internal diameter	110 mm
D - External diameter	240 mm
B - Bearing/Inner ring width	50 mm
a - Charge load application point	76 mm
rs - Min fillet radius	3 mm
r1s - Min fillet radius	1,1 mm
Radial clearance class	CN
Mass	9,6 kg

PRODUCT PERFORMANCE

C - Dynamic load	273000000 mN
C0 - Static load	246000000 mN
Cu - Fatigue limit load	14500000 mN
Nlim - Oil lubrication limit speed	25800 °/s
Nlim - Grease lubrication limit speed	19200 °/s
Tmax - Max operating temperature	393,15 °K

ABUTMENT

da min - Min shoulder diameter IR	124 mm
db min - Min IR shoulder diameter	117 mm
Da max - Max shoulder diameter OR	226 mm
Db max - Max OR shoulder diameter	233 mm
r1a - Max fillet radius	1 mm
ra max - Max shaft & housing fillet radius	2,5 mm



NTN Europe

1 rue des Usines · BP 2017 · 74010 Annecy Cedex · France · Tel. +33 (0)4 50 65 30 00
 S.A. au capital de 322 639 919 € · RCS ANNECY B 325 821 072 · Id. Fiscale : FR 48 325 821 072
 SIRET 325 821 072 00015 · Code APE 2815 Z · Code NACE 28.15

INDUSTRY CALCUL FACTORS

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

	e	Single or DT bearing arrangement				DB or DF arrangement			
		Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y	X	Y	X	Y
30°	0.8	1	0	0.9	0.76	1	0.78	0.63	1.24
40°	1.14			0.35	0.57		0.55	0.57	0.93

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

a	Single or DT bearing arrangement		DB or DF arrangement	
	X ₀	Y ₀	X ₀	Y ₀
30°	0.5	0.33	1	0.66
40°		0.26		0.52

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$

