

## SNx4LVC00A Quadruple 2-Input Positive-NAND Gates

### 1 Features

- Operate From 1.65 V to 3.6 V
- Specified From  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ ,  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ , and  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$
- Inputs Accept Voltages to 5.5 V
- Max  $t_{pd}$  of 4.3 ns at 3.3 V
- Typical  $V_{OLP}$  (Output Ground Bounce)  $< 0.8\text{ V}$  at  $V_{CC} = 3.3\text{ V}$ ,  $T_A = 25^{\circ}\text{C}$
- Typical  $V_{OHV}$  (Output  $V_{OH}$  Undershoot)  $> 2\text{ V}$  at  $V_{CC} = 3.3\text{ V}$ ,  $T_A = 25^{\circ}\text{C}$
- Latch-Up Performance Exceeds 250 mA Per JESD 17
- On Products Compliant to MIL-PRF-38535, All Parameters Are Tested Unless Otherwise Noted. On All Other Products, Production Processing Does Not Necessarily Include Testing of All Parameters.
- ESD Protection Exceeds JESD 22
  - 2000-V Human-Body Model
  - 200-V Machine Model
  - 1000-V Charged-Device Model

### 2 Applications

- AV Receivers
- Audio Docks: Portable
- Blu-ray Players and Home Theater
- MP3 Players or Recorder s
- Personal Digital Assistants (PDAs)
- Power: Telecom/Server AC/DC Supply: Single Controller: Analog and Digital
- Solid State Drives (SSDs): Client and Enterprise
- TVs: LCD, Digital, and High-Definition (HDTV)
- Tablets: Enterprise
- Video Analytics: Server
- Wireless Headsets, Keyboards, and Mice

### 3 Description

The SN54LVC00A quadruple 2-input positive-NAND gate is designed for 2.7-V to 3.6-V  $V_{CC}$  operation, and the SN74LVC00A quadruple 2-input positive-NAND gate is designed for 1.65-V to 3.6-V  $V_{CC}$  operation.

The SNx4LVC00A devices perform the Boolean function  $Y = \overline{A \times B}$  or  $Y = \overline{A} + \overline{B}$  in positive logic.


Inputs can be driven from either 3.3-V or 5-V devices. This feature allows the use of these devices as translators in a mixed 3.3-V/5-V system environment.

#### Device Information<sup>(1)</sup>

| PART NUMBER | PACKAGE    | BODY SIZE (NOM)    |
|-------------|------------|--------------------|
| SNx4LVC00A  | SOIC (14)  | 8.65 mm × 3.91 mm  |
|             | SSOP (14)  | 6.20 mm × 5.30 mm  |
|             | SOP (14)   | 10.30 mm × 5.30 mm |
|             | TSSOP (14) | 5.00 mm × 4.40 mm  |
|             | VQFN (14)  | 3.50 mm × 3.50 mm  |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

### 4 Simplified Schematic



## Table of Contents

|  |          |  |           |
|--|----------|--|-----------|
| <b>1 Features</b> .....                                | <b>1</b> | <b>8 Parameter Measurement Information</b> .....                 | <b>8</b>  |
| <b>2 Applications</b> .....                            | <b>1</b> | <b>9 Detailed Description</b> .....                              | <b>9</b>  |
| <b>3 Description</b> .....                             | <b>1</b> | 9.1 Overview .....   | 9         |
| <b>4 Simplified Schematic</b> .....                    | <b>1</b> | 9.2 Functional Block Diagram .....                               | 9         |
| <b>5 Revision History</b> .....                        | <b>2</b> | 9.3 Feature Description .....                                    | 9         |
| <b>6 Pin Configuration and Functions</b> .....         | <b>3</b> | 9.4 Device Functional Modes .....                                | 9         |
| <b>7 Specifications</b> .....                          | <b>4</b> | <b>10 Application and Implementation</b> .....                   | <b>10</b> |
| 7.1 Absolute Maximum Ratings .....                     | 4        | 10.1 Application Information .....                               | 10        |
| 7.2 ESD Ratings .....                                  | 4        | 10.2 Typical Application .....                                   | 10        |
| 7.3 Recommended Operating Conditions, SN54LVC00A ..... | 5        | <b>11 Power Supply Recommendations</b> .....                     | <b>11</b> |
| 7.4 Recommended Operating Conditions, SN74LVC00A ..... | 5        | <b>12 Layout</b> .....   | <b>11</b> |
| 7.5 Thermal Information .....                          | 6        | 12.1 Layout Guidelines .....                                     | 11        |
| 7.6 Electrical Characteristics, SN54LVC00A .....       | 6        | 12.2 Layout Example .....  | 11        |
| 7.7 Electrical Characteristics, SN74LVC00A .....       | 6        | <b>13 Device and Documentation Support</b> .....                 | <b>12</b> |
| 7.8 Switching Characteristics, SN54LVC00A .....        | 7        | 13.1 Related Links .....   | 12        |
| 7.9 Switching Characteristics, SN74LVC00A .....        | 7        | 13.2 Trademarks .....  | 12        |
| 7.10 Operating Characteristics .....                   | 7        | 13.3 Electrostatic Discharge Caution .....                       | 12        |
| 7.11 Typical Characteristics .....                     | 7        | 13.4 Glossary .....  | 12        |
|  |          | <b>14 Mechanical, Packaging, and Orderable Information</b> ..... | <b>12</b> |


## 5 Revision History

| <b>Changes from Revision Q (December 2014) to Revision R</b>  | <b>Page</b> |
|---|-------------|
| • Added Junction temperature row to <i>Absolute Maximum Ratings</i> table .....   | 4           |
| • Changed statement of "open drain" to "maximum sink and source current" statement in Overview of <i>Detailed Description</i> section ..... | 9           |
| • Deleted "open drain" from <i>Application Information</i> section .....  | 10          |


| <b>Changes from Revision P (July 2005) to Revision Q</b>   | <b>Page</b> |
|--|-------------|
| • Added <i>Applications</i> , <i>Device Information</i> table, <i>Pin Functions</i> table, <i>ESD Ratings</i> table, <i>Thermal Information</i> table, <i>Typical Characteristics</i> , <i>Feature Description</i> section, <i>Device Functional Modes</i> , <i>Application and Implementation</i> section, <i>Power Supply Recommendations</i> section, <i>Layout</i> section, <i>Device and Documentation Support</i> section, and <i>Mechanical, Packaging, and Orderable Information</i> section ..... | 1           |
| • Deleted <i>Ordering Information</i> table. ....  | 1           |
| • Added Military Disclaimer to <i>Features</i> . ....  | 1           |

## 6 Pin Configuration and Functions


SN54LVC00A . . . J OR W PACKAGE  
SN74LVC00A . . . D, DB, NS, OR PW PACKAGE  
(TOP VIEW)



SN54LVC00A . . . FK PACKAGE  
(TOP VIEW)



SN74LVC00A . . . RGY PACKAGE  
(TOP VIEW)



NC - No internal connection

### Pin Functions

| NAME            | PIN           |     |            |                               | TYPE | DESCRIPTION   |
|-----------------|---------------|-----|------------|-------------------------------|------|---------------|
|                 | SN74LVC00A    |     | SN54LVC00A |                               |      |               |
|                 | D, DB, NS, PW | RGY | J, W       | FK                            |      |               |
| 1A              | 1             | 1   | 1          | 2                             | I    | Gate 1 input  |
| 1B              | 2             | 2   | 2          | 3                             | I    | Gate 1 input  |
| 1Y              | 3             | 3   | 3          | 4                             | O    | Gate 1 output |
| 2A              | 4             | 4   | 4          | 6                             | I    | Gate 2 input  |
| 2B              | 5             | 5   | 5          | 8                             | I    | Gate 2 input  |
| 2Y              | 6             | 6   | 6          | 9                             | O    | Gate 2 output |
| GND             | 7             | 7   | 7          | 10                            | —    | Ground Pin    |
| 3Y              | 8             | 8   | 8          | 12                            | —    | Power Pin     |
| 3A              | 9             | 9   | 9          | 13                            | I    | Gate 4 input  |
| 3B              | 10            | 10  | 10         | 14                            | I    | Gate 4 input  |
| 4Y              | 11            | 11  | 11         | 16                            | O    | Gate 4 output |
| 4A              | 12            | 12  | 12         | 18                            | I    | Gate 3 input  |
| 4B              | 13            | 13  | 13         | 19                            | I    | Gate 3 input  |
| V <sub>CC</sub> | 14            | 14  | 14         | 20                            | O    | Gate 3 output |
| NC              | —             | —   | —          | 1<br>5<br>7<br>11<br>15<br>17 | —    | No Connection |

## 7 Specifications

### 7.1 Absolute Maximum Ratings

 over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                  |  | MIN                             | MAX                   | UNIT |    |
|------------------|--|---------------------------------|-----------------------|------|----|
| V <sub>CC</sub>  | Supply voltage range                   | -0.5                            | 6.5                   | V    |    |
| V <sub>I</sub>   | Input voltage range <sup>(2)</sup>     | -0.5                            | 6.5                   | V    |    |
| V <sub>O</sub>   | Output voltage range <sup>(2)(3)</sup> | -0.5                            | V <sub>CC</sub> + 0.5 | V    |    |
| I <sub>IK</sub>  | Input clamp current                    | V <sub>I</sub> < 0              | -50                   | mA   |    |
| I <sub>OK</sub>  | Output clamp current                   | V <sub>O</sub> < 0              | -50                   | mA   |    |
| I <sub>O</sub>   | Continuous output current              |                                 | ±50                   | mA   |    |
| V <sub>CC</sub>  | Continuous current through GND         |                                 | ±100                  | mA   |    |
| P <sub>tot</sub> | Power dissipation <sup>(4)(5)</sup>    | T <sub>A</sub> = -40°C to 125°C | 500                   | mW   |    |
| T <sub>stg</sub> | Storage temperature range              |                                 | -65                   | 150  | °C |
| T <sub>j</sub>   | Junction Temperature                   |                                 |                       | 150  | °C |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.
- (3) The value of V<sub>CC</sub> is provided in the *Recommended Operating Conditions* table.
- (4) For the D package: above 70°C, the value of P<sub>tot</sub> derates linearly with 8 mW/K.
- (5) For the DB, NS, and PW packages: above 60°C, the value of P<sub>tot</sub> derates linearly with 5.5 mW/K.

### 7.2 ESD Ratings

|  |   | VALUE | UNIT |
|--|---|-------|------|
| V <sub>(ESD)</sub>   | Electrostatic discharge   |       |      |
|  | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins <sup>(1)</sup> | 2000  | V    |
| Charged device model (CDM), per JEDEC specification JESD22-C101, all pins <sup>(2)</sup> | 1000  |       |      |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 7.3 Recommended Operating Conditions, SN54LVC00A

 over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                 |                           | SN54LVC00A                       |                 | UNIT |    |
|-----------------|---------------------------|----------------------------------|-----------------|------|----|
|                 |                           | –55°C to 125°C                   |                 |      |    |
|                 |                           | MIN                              | MAX             |      |    |
| V <sub>CC</sub> | Supply voltage            | Operating                        | 2               | 3.6  | V  |
|                 |                           | Data retention only              | 1.5             |      |    |
| V <sub>IH</sub> | High-level input voltage  | V <sub>CC</sub> = 2.7 V to 3.6 V |                 | 2    | V  |
| V <sub>IL</sub> | Low-level input voltage   | V <sub>CC</sub> = 2.7 V to 3.6 V |                 | 0.8  | V  |
| V <sub>I</sub>  | Input voltage             | 0                                | 5.5             |      | V  |
| V <sub>O</sub>  | Output voltage            | 0                                | V <sub>CC</sub> |      | V  |
| I <sub>OH</sub> | High-level output current | V <sub>CC</sub> = 2.7 V          |                 | –12  | mA |
|                 |                           | V <sub>CC</sub> = 3 V            |                 | –24  |    |
| I <sub>OL</sub> | Low-level output current  | V <sub>CC</sub> = 2.7 V          |                 | 12   | mA |
|                 |                           | V <sub>CC</sub> = 3 V            |                 | 24   |    |

(1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number [SCBA004](#).

### 7.4 Recommended Operating Conditions, SN74LVC00A

 over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                 |                           | SN74LVC00A                         |                        |               |                        |                |                        | UNIT |    |
|-----------------|---------------------------|------------------------------------|------------------------|---------------|------------------------|----------------|------------------------|------|----|
|                 |                           | T <sub>A</sub> = 25°C              |                        | –40°C to 85°C |                        | –40°C to 125°C |                        |      |    |
|                 |                           | MIN                                | MAX                    | MIN           | MAX                    | MIN            | MAX                    |      |    |
| V <sub>CC</sub> | Supply voltage            | Operating                          | 1.65                   | 3.6           | 1.65                   | 3.6            | 1.65                   | 3.6  | V  |
|                 |                           | Data retention only                | 1.5                    |               | 1.5                    |                | 1.5                    |      |    |
| V <sub>IH</sub> | High-level input voltage  | V <sub>CC</sub> = 1.65 V to 1.95 V | 0.65 × V <sub>CC</sub> |               | 0.65 × V <sub>CC</sub> |                | 0.65 × V <sub>CC</sub> |      | V  |
|                 |                           | V <sub>CC</sub> = 2.3 V to 2.7 V   | 1.7                    |               | 1.7                    |                | 1.7                    |      |    |
|                 |                           | V <sub>CC</sub> = 2.7 V to 3.6 V   | 2                      |               | 2                      |                | 2                      |      |    |
| V <sub>IL</sub> | Low-level input voltage   | V <sub>CC</sub> = 1.65 V to 1.95 V | 0.35 × V <sub>CC</sub> |               | 0.35 × V <sub>CC</sub> |                | 0.35 × V <sub>CC</sub> |      | V  |
|                 |                           | V <sub>CC</sub> = 2.3 V to 2.7 V   | 0.7                    |               | 0.7                    |                | 0.7                    |      |    |
|                 |                           | V <sub>CC</sub> = 2.7 V to 3.6 V   | 0.8                    |               | 0.8                    |                | 0.8                    |      |    |
| V <sub>I</sub>  | Input voltage             | 0                                  | 5.5                    | 0             | 5.5                    | 0              | 5.5                    | V    |    |
| V <sub>O</sub>  | Output voltage            | 0                                  | V <sub>CC</sub>        | 0             | V <sub>CC</sub>        | 0              | V <sub>CC</sub>        | V    |    |
| I <sub>OH</sub> | High-level output current | V <sub>CC</sub> = 1.65 V           |                        | –4            |                        | –4             |                        | –4   | mA |
|                 |                           | V <sub>CC</sub> = 2.3 V            |                        | –8            |                        | –8             |                        | –8   |    |
|                 |                           | V <sub>CC</sub> = 2.7 V            |                        | –12           |                        | –12            |                        | –12  |    |
|                 |                           | V <sub>CC</sub> = 3 V              |                        | –24           |                        | –24            |                        | –24  |    |
| I <sub>OL</sub> | Low-level output current  | V <sub>CC</sub> = 1.65 V           |                        | 4             |                        | 4              |                        | 4    | mA |
|                 |                           | V <sub>CC</sub> = 2.3 V            |                        | 8             |                        | 8              |                        | 8    |    |
|                 |                           | V <sub>CC</sub> = 2.7 V            |                        | 12            |                        | 12             |                        | 12   |    |
|                 |                           | V <sub>CC</sub> = 3 V              |                        | 24            |                        | 24             |                        | 24   |    |

(1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number [SCBA004](#).

## 7.5 Thermal Information

| THERMAL METRIC <sup>(1)</sup>                           | SN74LVC00A |         |         |         |         | UNIT |
|---|------------|---------|---------|---------|---------|------|
|   | D          | DB      | NS      | PW      | RGY     |      |
|   | 14 PINS    | 14 PINS | 14 PINS | 14 PINS | 14 PINS |      |
| R <sub>θJA</sub> Junction-to-ambient thermal resistance | 86         | 96      | 76      | 113     | 47      | °C/W |

(1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).

## 7.6 Electrical Characteristics, SN54LVC00A

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER        | TEST CONDITIONS  | V <sub>CC</sub> | SN54LVC00A            |     | UNIT |
|------------------|--|-----------------|-----------------------|-----|------|
|                  |  |                 | –55°C to 125°C        |     |      |
|                  |  |                 | MIN                   | MAX |      |
| V <sub>OH</sub>  | I <sub>OH</sub> = –100 μA  | 2.7 V to 3.6 V  | V <sub>CC</sub> – 0.2 |     | V    |
|                  | I <sub>OH</sub> = –12 mA   | 2.7 V           | 2.2                   |     |      |
|                  |  | 3 V             | 2.4                   |     |      |
|                  | I <sub>OH</sub> = –24 mA   | 3 V             | 2.2                   |     |      |
| V <sub>OL</sub>  | I <sub>OL</sub> = 100 μA   | 2.7 V to 3.6 V  | 0.2                   |     | V    |
|                  | I <sub>OL</sub> = 12 mA  | 2.7 V           | 0.4                   |     |      |
|                  | I <sub>OL</sub> = 24 mA  | 3 V             | 0.55                  |     |      |
| I <sub>I</sub>   | V <sub>I</sub> = 5.5 V or GND  | 3.6 V           | ±5                    |     | μA   |
| I <sub>CC</sub>  | V <sub>I</sub> = V <sub>CC</sub> or GND, I <sub>O</sub> = 0                  | 3.6 V           | 10                    |     | μA   |
| ΔI <sub>CC</sub> | One input at V <sub>CC</sub> – 0.6 V, Other inputs at V <sub>CC</sub> or GND | 2.7 V to 3.6 V  | 500                   |     | μA   |

## 7.7 Electrical Characteristics, SN74LVC00A

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER                | TEST CONDITIONS  | V <sub>CC</sub> | SN74LVC00A            |     |      |                       |     |                       | UNIT |     |
|--------------------------|--|-----------------|-----------------------|-----|------|-----------------------|-----|-----------------------|------|-----|
|                          |  |                 | T <sub>A</sub> = 25°C |     |      | –40°C to 85°C         |     | –40°C to 125°C        |      |     |
|                          |  |                 | MIN                   | TYP | MAX  | MIN                   | MAX | MIN                   |      | MAX |
| V <sub>OH</sub>          | I <sub>OH</sub> = –100 μA  | 1.65 V to 3.6 V | V <sub>CC</sub> – 0.2 |     |      | V <sub>CC</sub> – 0.2 |     | V <sub>CC</sub> – 0.3 |      | V   |
|                          | I <sub>OH</sub> = –4 mA  | 1.65 V          | 1.29                  |     |      | 1.2                   |     | 1.05                  |      |     |
|                          |  | 2.3 V           | 1.9                   |     |      | 1.7                   |     | 1.55                  |      |     |
|                          | I <sub>OH</sub> = –12 mA   | 2.7 V           | 2.2                   |     |      | 2.2                   |     | 2.05                  |      |     |
|                          |  | 3 V             | 2.4                   |     |      | 2.4                   |     | 2.25                  |      |     |
| I <sub>OH</sub> = –24 mA | 3 V  | 2.3             |                       |     | 2.2  |                       | 2   |                       |      |     |
| V <sub>OL</sub>          | I <sub>OL</sub> = 100 μA   | 1.65 V to 3.6 V | 0.1                   |     |      | 0.2                   |     | 0.3                   |      | V   |
|                          | I <sub>OL</sub> = 4 mA   | 1.65 V          | 0.24                  |     |      | 0.45                  |     | 0.6                   |      |     |
|                          |  | 2.3 V           | 0.3                   |     |      | 0.7                   |     | 0.85                  |      |     |
|                          | I <sub>OL</sub> = 12 mA  | 2.7 V           | 0.4                   |     |      | 0.4                   |     | 0.6                   |      |     |
|                          |  | 3 V             | 0.55                  |     |      | 0.55                  |     | 0.8                   |      |     |
| I <sub>OL</sub> = 24 mA  | 3 V  | 0.55            |                       |     | 0.55 |                       | 0.8 |                       |      |     |
| I <sub>I</sub>           | V <sub>I</sub> = 5.5 V or GND  | 3.6 V           | ±1                    |     |      | ±5                    |     | ±20                   |      | μA  |
| I <sub>CC</sub>          | V <sub>I</sub> = V <sub>CC</sub> or GND, I <sub>O</sub> = 0                  | 3.6 V           | 1                     |     |      | 10                    |     | 40                    |      | μA  |
| ΔI <sub>CC</sub>         | One input at V <sub>CC</sub> – 0.6 V, Other inputs at V <sub>CC</sub> or GND | 2.7 V to 3.6 V  | 500                   |     |      | 500                   |     | 5000                  |      | μA  |
| C <sub>i</sub>           | V <sub>I</sub> = V <sub>CC</sub> or GND                                      | 3.3 V           | 5                     |     |      |                       |     |                       |      | pF  |

### 7.8 Switching Characteristics, SN54LVC00A

over recommended operating free-air temperature range (unless otherwise noted) (see Figure 2)

| PARAMETER       | FROM (INPUT) | TO (OUTPUT) | V <sub>CC</sub> | SN54LVC00A     |     | UNIT |
|-----------------|--------------|-------------|-----------------|----------------|-----|------|
|                 |              |             |                 | –55°C to 125°C |     |      |
|                 |              |             |                 | MIN            | MAX |      |
| t <sub>pd</sub> | A or B       | Y           | 2.7 V           | 5.1            |     | ns   |
|                 |              |             | 3.3 V ± 0.3 V   | 1              | 4.3 |      |

### 7.9 Switching Characteristics, SN74LVC00A

over recommended operating free-air temperature range (unless otherwise noted) (see Figure 2)

| PARAMETER          | FROM (INPUT) | TO (OUTPUT) | V <sub>CC</sub> | SN74LVC00A            |     |     |               | UNIT |                |     |     |
|--------------------|--------------|-------------|-----------------|-----------------------|-----|-----|---------------|------|----------------|-----|-----|
|                    |              |             |                 | T <sub>A</sub> = 25°C |     |     | –40°C to 85°C |      | –40°C to 125°C |     |     |
|                    |              |             |                 | MIN                   | TYP | MAX | MIN           |      | MAX            | MIN | MAX |
| t <sub>pd</sub>    | A or B       | Y           | 1.8 V ± 0.15 V  | 1                     | 6   | 12  | 1             | 12.5 | 1              | 14  | ns  |
|                    |              |             | 2.5 V ± 0.2 V   | 1                     | 4.6 | 5.9 | 1             | 6.4  | 1              | 7.9 |     |
|                    |              |             | 2.7 V           | 1                     | 4.3 | 4.9 | 1             | 5.1  | 1              | 6.5 |     |
|                    |              |             | 3.3 V ± 0.3 V   | 1                     | 3.5 | 4.1 | 1             | 4.3  | 1              | 5.5 |     |
| t <sub>sk(o)</sub> |              |             | 3.3 V ± 0.3 V   |                       |     |     |               | 1    |                | 1.5 | ns  |

### 7.10 Operating Characteristics

T<sub>A</sub> = 25°C

| PARAMETER  | TEST CONDITIONS | V <sub>CC</sub> | TYP | UNIT |
|--|-----------------|-----------------|-----|------|
| C <sub>pd</sub> Power dissipation capacitance per gate | f = 10 MHz      | 1.8 V           | 18  | pF   |
|  |                 | 2.5 V           | 18  |      |
|  |                 | 3.3 V           | 19  |      |

### 7.11 Typical Characteristics









Figure 1. TPD vs V<sub>CC</sub> (T<sub>A</sub> = 25°C)

## 8 Parameter Measurement Information


**LOAD CIRCUIT**

| TEST              | S1         |
|-------------------|------------|
| $t_{PLH}/t_{PHL}$ | Open       |
| $t_{PLZ}/t_{PZL}$ | $V_{LOAD}$ |
| $t_{PHZ}/t_{PZH}$ | GND        |

| $V_{CC}$                         | INPUTS   |                      | $V_M$      | $V_{LOAD}$        | $C_L$ | $R_L$        | $V_{\Delta}$ |
|----------------------------------|----------|----------------------|------------|-------------------|-------|--------------|--------------|
|                                  | $V_I$    | $t_r/t_f$            |            |                   |       |              |              |
| $1.8\text{ V} \pm 0.15\text{ V}$ | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30 pF | 1 k $\Omega$ | 0.15 V       |
| $2.5\text{ V} \pm 0.2\text{ V}$  | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30 pF | 500 $\Omega$ | 0.15 V       |
| 2.7 V                            | 2.7 V    | $\leq 2.5\text{ ns}$ | 1.5 V      | 6 V               | 50 pF | 500 $\Omega$ | 0.3 V        |
| $3.3\text{ V} \pm 0.3\text{ V}$  | 2.7 V    | $\leq 2.5\text{ ns}$ | 1.5 V      | 6 V               | 50 pF | 500 $\Omega$ | 0.3 V        |


**VOLTAGE WAVEFORMS  
PULSE DURATION**

**VOLTAGE WAVEFORMS  
SETUP AND HOLD TIMES**

**VOLTAGE WAVEFORMS  
PROPAGATION DELAY TIMES  
INVERTING AND NONINVERTING OUTPUTS**

**VOLTAGE WAVEFORMS  
ENABLE AND DISABLE TIMES  
LOW- AND HIGH-LEVEL ENABLING**

- NOTES:
- $C_L$  includes probe and jig capacitance.
  - Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
  - All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10\text{ MHz}$ ,  $Z_O = 50\ \Omega$ .
  - The outputs are measured one at a time, with one transition per measurement.
  - $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
  - $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .
  - $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .
  - All parameters and waveforms are not applicable to all devices.

**Figure 2. Load Circuit and Voltage Waveforms**



## 9 Detailed Description

### 9.1 Overview

The maximum sink and source current is 24mA.

Inputs can be driven from 1.8-V, 2.5-V, 3.3-V (LVTTTL), or 5-V (CMOS) devices. This feature allows the use of this device as translators in a mixed-system environment.

This device is fully specified for partial-power-down applications using  $I_{off}$ . The  $I_{off}$  circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.

### 9.2 Functional Block Diagram

Logic Diagram, Each Gate (Positive Logic)



### 9.3 Feature Description

- Wide operating voltage range
  - Operates from 1.65 V to 3.6 V
- Allows up or down voltage translation
  - Inputs and outputs accept voltages to 5.5 V
- $I_{off}$  feature
  - Allows voltages on the inputs and outputs when  $V_{CC}$  is 0 V

### 9.4 Device Functional Modes

Table 1. Function Table  
(Each Gate)

| INPUTS |   | OUTPUT |
|--------|---|--------|
| A      | B | Y      |
| H      | H | L      |
| L      | X | H      |
| X      | L | H      |

## 10 Application and Implementation


### NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 10.1 Application Information

SN74LVC00A is a high-drive CMOS device that can be used for a multitude of buffer-type functions. It can produce 24 mA of drive current at 3.3 V. Therefore, this device is ideal for driving multiple inputs and for high-speed applications up to 100 MHz. The inputs and outputs are 5.5-V tolerant allowing the device to translate up to 5.5 V or down to  $V_{CC}$ .

### 10.2 Typical Application



**Figure 3. Typical NAND Gate Application and Supply Voltage**

#### 10.2.1 Design Requirements

This device uses CMOS technology and has balanced output drive. Care should be taken to avoid bus contention because it can drive currents that would exceed maximum limits. The high drive will also create fast edges into light loads; therefore, routing and load conditions should be considered to prevent ringing.

#### 10.2.2 Detailed Design Procedure

1. Recommended Input Conditions
  - Rise time and fall time specs: See  $(\Delta t/\Delta V)$  in the [Recommended Operating Conditions, SN74LVC00A](#) table.
  - Specified high and low levels: See ( $V_{IH}$  and  $V_{IL}$ ) in the [Recommended Operating Conditions, SN74LVC00A](#) table.
  - Inputs are overvoltage tolerant allowing them to go as high as 5.5 V at any valid  $V_{CC}$ .
2. Recommend Output Conditions
  - Load currents should not exceed 25 mA per output and 50 mA total for the part.
  - Outputs should not be pulled above 5.5 V.

## Typical Application (continued)

### 10.2.3 Application Curves




Figure 4.  $I_{CC}$  vs Frequency

## 11 Power Supply Recommendations

The power supply can be any voltage between the MIN and MAX supply voltage rating located in the [Recommended Operating Conditions, SN74LVC00A](#) table.

Each  $V_{CC}$  pin should have a good bypass capacitor to prevent power disturbance. For devices with a single supply, 0.1  $\mu\text{F}$  is recommended; if there are multiple  $V_{CC}$  pins, then 0.01  $\mu\text{F}$  or 0.022  $\mu\text{F}$  is recommended for each power pin. It is acceptable to parallel multiple bypass caps to reject different frequencies of noise. A 0.1  $\mu\text{F}$  and a 1  $\mu\text{F}$  are commonly used in parallel. The bypass capacitor should be installed as close to the power pin as possible for best results.

## 12 Layout

### 12.1 Layout Guidelines

When using multiple bit logic devices inputs should never float.

In many cases, functions or parts of functions of digital logic devices are unused, for example, when only two inputs of a triple-input AND gate are used or only 3 of the 4 buffer gates are used. Such input pins should not be left unconnected because the undefined voltages at the outside connections result in undefined operational states. [Layout Example](#) specifies the rules that must be observed under all circumstances. All unused inputs of digital logic devices must be connected to a high or low bias to prevent them from floating. The logic level that should be applied to any particular unused input depends on the function of the device. Generally they will be tied to GND or  $V_{CC}$ , whichever makes more sense or is more convenient. It is generally acceptable to float outputs, unless the part is a transceiver.

### 12.2 Layout Example




Figure 5. Layout Diagram

## 13 Device and Documentation Support

### 13.1 Related Links

The table below lists quick access links. Categories include technical documents, support and community resources, tools and software, and quick access to sample or buy.

**Table 2. Related Links**

| PARTS      | PRODUCT FOLDER             | SAMPLE & BUY               | TECHNICAL DOCUMENTS        | TOOLS & SOFTWARE           | SUPPORT & COMMUNITY        |
|------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| SN54LVC00A | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| SN74LVC00A | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |

### 13.2 Trademarks

All trademarks are the property of their respective owners.

### 13.3 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

### 13.4 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 14 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2)  | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)          | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|------------------|--------------------------------------|----------------------|--------------|----------------------------------|-------------------------|
| 5962-9753301Q2A  | ACTIVE        | LCCC         | FK              | 20   | 55          | Non-RoHS & Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-9753301Q2A<br>SNJ54LVC00AFK | <a href="#">Samples</a> |
| 5962-9753301QCA  | ACTIVE        | CDIP         | J               | 14   | 25          | Non-RoHS & Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-9753301QCA<br>SNJ54LVC00AJ  | <a href="#">Samples</a> |
| 5962-9753301QDA  | ACTIVE        | CFP          | W               | 14   | 25          | Non-RoHS & Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-9753301QDA<br>SNJ54LVC00AW  | <a href="#">Samples</a> |
| 5962-9753301VDA  | ACTIVE        | CFP          | W               | 14   | 25          | Non-RoHS & Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-9753301VDA<br>SNV54LVC00AW  | <a href="#">Samples</a> |
| SN74LVC00AD      | ACTIVE        | SOIC         | D               | 14   | 50          | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LVC00A                           | <a href="#">Samples</a> |
| SN74LVC00ADBR    | ACTIVE        | SSOP         | DB              | 14   | 2000        | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                            | <a href="#">Samples</a> |
| SN74LVC00ADBRG4  | ACTIVE        | SSOP         | DB              | 14   | 2000        | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                            | <a href="#">Samples</a> |
| SN74LVC00ADE4    | ACTIVE        | SOIC         | D               | 14   | 50          | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LVC00A                           | <a href="#">Samples</a> |
| SN74LVC00ADR     | ACTIVE        | SOIC         | D               | 14   | 2500        | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LVC00A                           | <a href="#">Samples</a> |
| SN74LVC00ADRG4   | ACTIVE        | SOIC         | D               | 14   | 2500        | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LVC00A                           | <a href="#">Samples</a> |
| SN74LVC00ADT     | ACTIVE        | SOIC         | D               | 14   | 250         | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LVC00A                           | <a href="#">Samples</a> |
| SN74LVC00ANSR    | ACTIVE        | SO           | NS              | 14   | 2000        | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LVC00A                           | <a href="#">Samples</a> |
| SN74LVC00ANSRG4  | ACTIVE        | SO           | NS              | 14   | 2000        | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LVC00A                           | <a href="#">Samples</a> |
| SN74LVC00APW     | ACTIVE        | TSSOP        | PW              | 14   | 90          | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                            | <a href="#">Samples</a> |
| SN74LVC00APWE4   | ACTIVE        | TSSOP        | PW              | 14   | 90          | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                            | <a href="#">Samples</a> |
| SN74LVC00APWG4   | ACTIVE        | TSSOP        | PW              | 14   | 90          | RoHS & Green     | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                            | <a href="#">Samples</a> |
| SN74LVC00APWR    | ACTIVE        | TSSOP        | PW              | 14   | 2000        | RoHS & Green     | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 125   | LC00A                            | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2)     | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)              | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|---------------------|--------------------------------------|----------------------|--------------|--------------------------------------|-------------------------|
| SN74LVC00APWRE4  | ACTIVE        | TSSOP        | PW              | 14   | 2000        | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                                | <a href="#">Samples</a> |
| SN74LVC00APWRG4  | ACTIVE        | TSSOP        | PW              | 14   | 2000        | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                                | <a href="#">Samples</a> |
| SN74LVC00APWT    | ACTIVE        | TSSOP        | PW              | 14   | 250         | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | LC00A                                | <a href="#">Samples</a> |
| SN74LVC00ARGYR   | ACTIVE        | VQFN         | RGY             | 14   | 3000        | RoHS & Green        | NIPDAU                               | Level-2-260C-1 YEAR  | -40 to 125   | LC00A                                | <a href="#">Samples</a> |
| SNJ54LVC00AFK    | ACTIVE        | LCCC         | FK              | 20   | 55          | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-9753301Q2A<br>SNJ54LVC<br>00AFK | <a href="#">Samples</a> |
| SNJ54LVC00AJ     | ACTIVE        | CDIP         | J               | 14   | 25          | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-9753301QC<br>A<br>SNJ54LVC00AJ  | <a href="#">Samples</a> |
| SNJ54LVC00AW     | ACTIVE        | CFP          | W               | 14   | 25          | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-9753301QD<br>A<br>SNJ54LVC00AW  | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN54LVC00A, SN54LVC00A-SP, SN74LVC00A :**

- Catalog : [SN74LVC00A](#), [SN54LVC00A](#)
  
- Automotive : [SN74LVC00A-Q1](#), [SN74LVC00A-Q1](#)
  
- Enhanced Product : [SN74LVC00A-EP](#), [SN74LVC00A-EP](#)
  
- Military : [SN54LVC00A](#)
  
- Space : [SN54LVC00A-SP](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
  
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
  
- Enhanced Product - Supports Defense, Aerospace and Medical Applications
  
- Military - QML certified for Military and Defense Applications
  
- Space - Radiation tolerant, ceramic packaging and qualified for use in Space-based application

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

| Device          | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LVC00ADBR   | SSOP         | DB              | 14   | 2000 | 330.0              | 16.4               | 8.35    | 6.6     | 2.4     | 12.0    | 16.0   | Q1            |
| SN74LVC00ADR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LVC00ADT    | SOIC         | D               | 14   | 250  | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LVC00ANSR   | SO           | NS              | 14   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |
| SN74LVC00APWR   | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74LVC00APWRG4 | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74LVC00APWT   | TSSOP        | PW              | 14   | 250  | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74LVC00ARGYR  | VQFN         | RGY             | 14   | 3000 | 330.0              | 12.4               | 3.75    | 3.75    | 1.15    | 8.0     | 12.0   | Q1            |



## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device          | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LVC00ADBR   | SSOP         | DB              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| SN74LVC00ADR    | SOIC         | D               | 14   | 2500 | 333.2       | 345.9      | 28.6        |
| SN74LVC00ADT    | SOIC         | D               | 14   | 250  | 210.0       | 185.0      | 35.0        |
| SN74LVC00ANSR   | SO           | NS              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| SN74LVC00APWR   | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| SN74LVC00APWRG4 | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| SN74LVC00APWT   | TSSOP        | PW              | 14   | 250  | 356.0       | 356.0      | 35.0        |
| SN74LVC00ARGYR  | VQFN         | RGY             | 14   | 3000 | 356.0       | 356.0      | 35.0        |

**TUBE**


\*All dimensions are nominal

| Device          | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-----------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 5962-9753301Q2A | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| 5962-9753301QDA | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| 5962-9753301VDA | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| SN74LVC00AD     | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LVC00ADE4   | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LVC00APW    | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SN74LVC00APWE4  | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SN74LVC00APWG4  | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SNJ54LVC00AFK   | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| SNJ54LVC00AW    | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |

## GENERIC PACKAGE VIEW


**FK 20**

**LCCC - 2.03 mm max height**

8.89 x 8.89, 1.27 mm pitch

LEADLESS CERAMIC CHIP CARRIER

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4229370VA\

J 14

**GENERIC PACKAGE VIEW**  
**CDIP - 5.08 mm max height**  
CERAMIC DUAL IN LINE PACKAGE



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4040083-5/G

J0014A



# PACKAGE OUTLINE

CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE



4214771/A 05/2017

NOTES:

1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermetically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
5. Falls within MIL-STD-1835 and GDIP1-T14.

# EXAMPLE BOARD LAYOUT

J0014A

CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE



LAND PATTERN EXAMPLE  
NON-SOLDER MASK DEFINED  
SCALE: 5X





4214771/A 05/2017

D (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4040047-5/M 06/11

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  -  Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
  -  Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
  - E. Reference JEDEC MS-012 variation AB.

D (R-PDSO-G14)

PLASTIC SMALL OUTLINE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.





PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4211284-2/G 08/15

- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.



RGY (S-PVQFN-N14)

PLASTIC QUAD FLATPACK NO-LEAD



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. QFN (Quad Flatpack No-Lead) package configuration.
  - D. The package thermal pad must be soldered to the board for thermal and mechanical performance.
  - E. See the additional figure in the Product Data Sheet for details regarding the exposed thermal pad features and dimensions.
  - F. Pin 1 identifiers are located on both top and bottom of the package and within the zone indicated. The Pin 1 identifiers are either a molded, marked, or metal feature.
  - G. Package complies to JEDEC MO-241 variation BA.

RGY (S-PVQFN-N14)

PLASTIC QUAD FLATPACK NO-LEAD

**THERMAL INFORMATION**

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271. This document is available at [www.ti.com](http://www.ti.com).

The exposed thermal pad dimensions for this package are shown in the following illustration.



Bottom View

Exposed Thermal Pad Dimensions

4206353-2/P 03/14

NOTE: All linear dimensions are in millimeters

RGY (S-PVQFN-N14)

PLASTIC QUAD FLATPACK NO-LEAD



4208122-2/P 03/14

- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - This package is designed to be soldered to a thermal pad on the board. Refer to Application Note, Quad Flat-Pack QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at [www.ti.com](http://www.ti.com) <<http://www.ti.com>>.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
  - Customers should contact their board fabrication site for minimum solder mask web tolerances between signal pads.

## MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

W (R-GDFP-F14)

CERAMIC DUAL FLATPACK



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package can be hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only.
  - E. Falls within MIL STD 1835 GDFP1-F14



## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2024, Texas Instruments Incorporated