

# PM-7200 Module Series

Gigabit and Fast Ethernet modules for PT Series rackmount Ethernet switches



## Features and Benefits

- -40 to 85°C wide operating temperature
- IEC 61850-3 and IEEE 1613 compliant

## Certifications



## Introduction

The PM-7200 Module Series includes Gigabit and Fast Ethernet modules for the PT Series rackmount Ethernet switches. IEEE 1588 interface modules provide hardware-based PTP functions for precise time synchronization across the network.

## Specifications

### Ethernet Software Features

Time Management	PTP models: IEEE 1588 PTP v1/v2 (hardware-based)
Redundancy Protocols	PM-7200-PHR-PTP Series: HSR, PRP

### Ethernet Interface

Combo Ports (10/100/1000BaseT(X) or 1000BaseSFP)	PM-7200-2GTXSFP: 2 PM-7200-4GTXSFP: 4
10/100/1000BaseT(X) Ports PRP/HSR Ports	PM-7200-4GTX-PHR-PTP: 2
100/1000BaseSFP PRP/HSR Ports	PM-7200-4GSFP-PHR-PTP: 2
10/100/1000BaseT(X) Ports (RJ45 connector)	PM-7200-4GTX-PHR-PTP: 2
100/1000BaseSFP Ports	PM-7200-4GSFP-PHR-PTP: 2
10/100BaseT(X) Ports (RJ45 connector)	PM-7200-2TX Series: 2 PM-7200-4TX Series: 4 PM-7200-8TX: 8
10/100BaseT(X) Ports (M12 D-coded 4-pin female connector)	PM-7200-4M12: 4
100BaseSFP Slots	PM-7200-8SFP: 8
100BaseFX Ports (multi-mode SC connector)	PM-7200-1MSC: 1 PM-7200-2MSC Series: 2 PM-7200-4MS Series: 4 PM-7200-6MSC: 6
100BaseFX Ports (multi-mode ST connector)	PM-7200-1MST: 1 PM-7200-2MST Series: 2

	PM-7200-4MST Series: 4 PM-7200-6MST: 6																																					
100BaseFX Ports (single-mode SC connector)	PM-7200-2SSC Series: 2 PM-7200-4SSC2TX: 4 PM-7200-6SSC: 6																																					
100BaseFX Ports, Multi-Mode MTRJ Connector	PM-7200-8MTRJ: 8																																					
PPS Output, BNC Connector	PM-7200-1BNC2MST-PTP: 1																																					
Optical Fiber	<table border="1"> <thead> <tr> <th rowspan="3">Fiber Cable Type</th> <th colspan="3">100BaseFX</th> </tr> <tr> <th colspan="2">Multi-Mode</th> <th>Single-Mode</th> </tr> <tr> <th>OM1</th> <th>50/125 μm 800 MHz x km</th> <th>G.652</th> </tr> </thead> <tbody> <tr> <td>Typical Distance</td> <td>4 km</td> <td>5 km</td> <td>40 km</td> </tr> <tr> <td rowspan="3">Wavelength</td> <td>Typical (nm)</td> <td>1300</td> <td>1310</td> </tr> <tr> <td>TX Range (nm)</td> <td>1260 to 1360</td> <td>1280 to 1340</td> </tr> <tr> <td>RX Range (nm)</td> <td>1100 to 1600</td> <td>1100 to 1600</td> </tr> <tr> <td rowspan="4">Optical Power</td> <td>TX Range (dBm)</td> <td>-10 to -20</td> <td>0 to -5</td> </tr> <tr> <td>RX Range (dBm)</td> <td>-3 to -32</td> <td>-3 to -34</td> </tr> <tr> <td>Link Budget (dB)</td> <td>12</td> <td>29</td> </tr> <tr> <td>Dispersion Penalty (dB)</td> <td>3</td> <td>1</td> </tr> </tbody> </table> <p>Note: When connecting a single-mode fiber transceiver, we recommend using an attenuator to prevent damage caused by excessive optical power. Note: Compute the “typical distance” of a specific fiber transceiver as follows: Link budget (dB) &gt; dispersion penalty (dB) + total link loss (dB).</p>	Fiber Cable Type	100BaseFX			Multi-Mode		Single-Mode	OM1	50/125 μm 800 MHz x km	G.652	Typical Distance	4 km	5 km	40 km	Wavelength	Typical (nm)	1300	1310	TX Range (nm)	1260 to 1360	1280 to 1340	RX Range (nm)	1100 to 1600	1100 to 1600	Optical Power	TX Range (dBm)	-10 to -20	0 to -5	RX Range (dBm)	-3 to -32	-3 to -34	Link Budget (dB)	12	29	Dispersion Penalty (dB)	3	1
	Fiber Cable Type		100BaseFX																																			
			Multi-Mode		Single-Mode																																	
		OM1	50/125 μm 800 MHz x km	G.652																																		
	Typical Distance	4 km	5 km	40 km																																		
	Wavelength	Typical (nm)	1300	1310																																		
		TX Range (nm)	1260 to 1360	1280 to 1340																																		
		RX Range (nm)	1100 to 1600	1100 to 1600																																		
	Optical Power	TX Range (dBm)	-10 to -20	0 to -5																																		
		RX Range (dBm)	-3 to -32	-3 to -34																																		
		Link Budget (dB)	12	29																																		
		Dispersion Penalty (dB)	3	1																																		

## Warranty

Warranty Period	5 years
Details	See <a href="http://www.moxa.com/warranty">www.moxa.com/warranty</a>

## Package Contents

Device	1 x PM-7200 Series module
Documentation	1 x warranty card 1 x product certificates of quality inspection, Simplified Chinese 1 x product notice, Simplified Chinese

## Ordering Information

Model Name	1000 Mbps	100 Mbps	PPS Output	Hardware-Based IEEE 1588 PTP V2	PRP/HSR	Operating Temp.
PM-7200-1MSC	-	1 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-1MST	-	1 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-2GTXSFP	2 x combo port, 10/100/1000BaseT(X) or 1000BaseSFP	-	-	-	-	-45 to 85°C
PM-7200-2MSC	-	2 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C

Model Name	1000 Mbps	100 Mbps	PPS Output	Hardware-Based IEEE 1588 PTP V2	PRP/HSR	Operating Temp.
PM-7200-2MSC4TX	-	4 x 10/100BaseT(X) 2 x 1000BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-2MST	-	2 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-2MST4TX	-	4 x 10/100BaseT(X) 2 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-2SSC	-	2 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-2SSC4TX	-	4 x 10/100BaseT(X) 2 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-4GTXSFP	4 x combo port, 10/100/1000BaseT(X) or 1000BaseSFP	-	-	-	-	-45 to 85°C
PM-7200-4M12	-	4 x 10/100BaseT(X), M12 connectors	-	-	-	-45 to 85°C
PM-7200-4MSC2TX	-	2 x 10/100BaseT(X) 4 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-4MST2TX	-	2 x 10/100BaseT(X) 4 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-4SSC2TX	-	2 x 10/100BaseT(X) 4 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-6MSC	-	6 x 100BaseFX, multi-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-6MST	-	6 x 100BaseFX, multi-mode, ST connector	-	-	-	-45 to 85°C
PM-7200-6SSC	-	6 x 100BaseFX, single-mode, SC connector	-	-	-	-45 to 85°C
PM-7200-8SFP	-	8 x 100BaseFX	-	-	-	-45 to 85°C
PM-7200-8TX	-	8 x 10/100BaseT(X)	-	-	-	-45 to 85°C
PM-7200-1BNC2MST-PTP	-	2 x 100BaseFX, multi-mode, ST connector	1 x BNC connector	-	-	-45 to 85°C
PM-7200-8MTRJ	-	8 x 100BaseFX, multi-mode, MTRJ connector	-	-	-	-45 to 85°C
PM-7200-4TX-PTP	-	4 x 10/100BaseT(X)	-	✓	-	-45 to 85°C
PM-7200-4MST-PTP	-	4 x 100BaseFX, multi-mode, ST connector	-	✓	-	-45 to 85°C
PM-7200-4MSC-PTP	-	4 x 100BaseFX, multi-mode, SC connector	-	✓	-	-45 to 85°C
PM-7200-4GTX-PHR-PTP	2 x 10/100/1000BaseT(X)	-	-	✓	2 x 10/100/1000BaseT(X) PRP/HSR ports	-45 to 85°C
PM-7200-4GSFP-PHR-PTP	2 x 100/1000BaseSFP	-	-	✓	2 x 100/1000BaseSFP PRP/HSR ports	-45 to 85°C

## Accessories (sold separately)

### SFP Modules

SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode with LC connector for 4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1GEZXC	SFP module with 1 1000BaseEZXC port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXC-120	SFP module with 1 1000BaseEZXC port with LC connector for 120 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature
SFP-1GLHXC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature
SFP-1GLHXC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GLSXC	SFP module with 1 1000BaseLSX port with LC connector for 500 m transmission, 0 to 60°C operating temperature
SFP-1GLSXC-T	SFP module with 1 1000BaseLSX port with LC connector for 500 m transmission, -40 to 85°C operating temperature
SFP-1GLXLC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature
SFP-1GLXLC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GSXC	SFP module with 1 1000BaseSX port with LC connector for 300/550 m transmission, 0 to 60°C operating temperature

SFP-1GSXLC-T	SFP module with 1 1000BaseSX port with LC connector for 300/550 m transmission, -40 to 85°C operating temperature
SFP-1GZXLC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature
SFP-1GZXLC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature

© Moxa Inc. All rights reserved. Updated Apr 25, 2019.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.