



### Two-Component Adhesive for Heat Shrinkable Tubing and Shapes

V9500

#### Features and benefits

- High performance, two-part epoxy adhesive
- Very resistant to most solvents and fuels, even at elevated temperatures
- Two different packages available
- V9500 available in 10 g sachets for manual mixing
- Processing set: emery paper, small mixing bowl and wooden spatula
- High performance bonding
- Meets military requirements for heat shrinkable components for harnesses



Two-component epoxy adhesive V9500.



For Material / Adhesive information please refer to page 260, 261.



The V9500 applicator gun guarantees the clean and precise coating of special fittings.

<b>MATERIAL</b>	Epoxy resins (EP)
<b>Colour</b>	Black (BK)
<b>Curing Temperature</b>	+135 °C
<b>Curing Time</b>	24 hours at +25 °C, 2 hours at +85 °C
<b>Operating Temperature</b>	-75 °C to +150 °C



TYPE	Description	Designation as per VG-Norm	Article-No.
<b>V9500 Epoxy Kit</b>	5 x 10 g sachets (50 g), 5 x mixing pots, 5 x mixing sticks, 5 x emery papers	VG 95343 T15 A 001 A	627-95000
	1 x dual cartridge, 5 x mixing pots, 5 x mixing sticks, 5 x emery papers	VG 95343 T15 A 002 B	627-95001
<b>V9500 Epoxy Cartridge</b>	Two-component adhesive cartridge	VG 95343 T15 A	627-95002
<b>V9500 Applicator Gun</b>	Applicator gun	VG 95343 T15 DA	627-95003
<b>V9500 Applicator Nozzle</b>	Mixing nozzle	VG 95343 T15 MA	627-95004

All dimensions in mm. Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.