

FEATURES

- 3-line backlit display
- Best in class:
Vacuum precision
- Very fast!
- Wide temperature
compensation for use
in cooled places
- High resolution and
precision
- Excellent
price/performance
ratio
- Waterproof (IP67)
- Durable with long
battery life
- Easy to use universal
pressure port with
exchangeable
connection
- Modern compact
housing

RS PRO Manometer / Vacuum meter

RS Stock No.: 205-0961



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Manometer

Product Description

Manometer / Vacuum meter for fast and precise measurements in vacuum

- packaging machine testing
- perfect for monitoring vacuum cast processes of e.g. composite materials
- traceable reference for ambient conditions / meteorology

Universal pressure connection:

- equipped with barbed port for 6 mm and 8 mm hoses
- Port can be adapted to Your special needs by exchanging to many standard G1/8 inch ports like available in pneumatic accessories

Selectable special functions:

- NULL / Tare function
- AVR: Averaging over 2 s / 5 s / 10 s for stable display of fluctuating pressures

General Specifications

Model Name	RS 1111
Pressure Port Type	Absolute UT connection for tubes 6 x 1 mm (4 mm inner) and 8 x 1 mm (6 mm inner)
Number of Pressure Ports	1
Pressure Range	0.0..1700.0 hPa (mbar)
Selectable Units	hPa / mbar / mmHg / psi
Resolution	0.1 hPa
Response Time	< 1s
Over Range Indicator	Yes
Under Range Indicator	Yes
Zero Pressure Correction	Yes
Maximum Overpressure	2500 hPa abs
Alarm	No
Best Accuracy	+/- 2 hPa (@ 0..50 °C)
Display Type	Backlit LCD
Data Logging	No
Leak Testing	No
Low Battery Indicator	Yes
Minimum / Maximum Recordings	Yes, with "Hold" function
Intrinsically Safe	No
Interface	N/A
Calibration Available	Factory calibration protocol
Applications	Vacuum packaging machines, vacuum cast, vacuum infusion, ambient conditions of labs

Electrical Specifications

Battery Type	2 x AA
Battery Life	3000 h
Plug Type	UT connection for tubes 6 x 1 mm (4 mm inner) and 8 x 1 mm (6 mm inner)
Auto Power Off time	15 minutes, 30, 60, 120, or 240 minutes, or can be disabled
Low Battery Indicator	Yes

Mechanical Specifications

Housing Material	Break-proof ABS housing
Connection Thread Standard	one tube connection, interchangeable with G1/8 universal port
Connection Thread Size	G1/8
Dimensions	108.0 mm x 54.0 mm x 28.0 mm
Length	28 mm
Width	54 mm
Height	108 mm
Weight	140 g
Vibration Resistance	Not specified
Shock Resistance	Not specified

Operation Environment Specifications

Relative Humidity	95 % r.h. temporarily 100 % r.h. both non-condensing
Minimum Operating Temperature	-20 °C
Maximum Operating Temperature	+50 °C
Storage Temperature Range	-20 to +70 °C

Protection Category

IP Protection	IP 67
---------------	-------

Additional Information

EAN	4058175682862
Custom Tariff Number	90278020

Approvals

Compliance/Certifications	CE
Declarations	Manufacturer Conformity

Similar Products

Stock No.	RS#	RS#	RS#
Model Number	RS 1114		
Pressure Port Type	absolute / relative		
Number of Pressure Ports	1		
Pressure Range	0..14000 hPa (mbar)		
Selectable Units	hPa / mbar / mmHg / psi		
Resolution	1 hPa		
Response Time	< 1s		
Over Range Indicator	Yes		
Under Range Indicator	Yes		
Zero Pressure Correction	Yes		
Maximum Overpressure	20000 hPa abs		
Alarm	No		
Best Accuracy	+/- 0.1 % FSS or +/-0.1 % of value (@ 25 °C)		
Display Type	Backlit LCD		
Data Logging	No		
Leak Testing	No		
Low Battery Indicator	Yes		
Minimum / Maximum Recordings	Yes, with "Hold" function		



Exchangeable pressure port