

Inline terminal - IB IL EX-IS AIO 4/EF-PAC - 2869912

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Inline intrinsically safe analog I/O terminal, 4 configurable input/output channels, complete with accessories

Why buy this product

- Fieldbus-independent diagnostics using FDT/DTM technology
- Module-based electrical isolation
- Output: 0/4 ... 20 mA
- Input: 0 ... 10 V, 0/4 ... 20 mA
- 4 configurable I/O channels
- Single-channel diagnostics



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 470216
GTIN	4046356470216

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	48.8 mm
Height	136.8 mm
Depth	71.5 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

Inline terminal - IB IL EX-IS AIO 4/EF-PAC - 2869912

Technical data

Ambient conditions

Permissible humidity (operation)	10 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection	IP20
	IP20

General

Mounting type	DIN rail
Net weight	222 g

Interfaces

Designation	Inline local bus
Connection method	Inline data jumper
Transmission speed	500 kbps

Inline potentials

Designation	Communications power (U_L)
Supply voltage	5 V DC (via voltage jumper)
Current consumption	max. 50 mA
Supply voltage	28 V DC
Current consumption	max. 187 mA
Power consumption	4.7 W (per channel)

Analog inputs

Input name	Analog inputs
Number of inputs	4
Connection method	Inline shield connector
Connection technology	2, 3-wire
Resolution A/D	16 bit (15 bit + sign bit)
Type of protection	Polarity protection, surge protection
Data formats	IB IL, standardized representation, S7 compatible
Current input signal	0 mA ... 20 mA
	4 mA ... 20 mA
Voltage input signal	0 V DC ... 10 V DC
	0 V ... 10 V
Current input signal	0 mA ... 20 mA
	4 mA ... 20 mA

Analog outputs

Number of outputs	4 (Can be configured as input or output)
Connection method	Inline shield connector
Connection technology	2-wire
Type of protection	Polarity protection, surge protection
Data formats	IB IL, standardized representation, S7 compatible

Inline terminal - IB IL EX-IS AIO 4/EF-PAC - 2869912

Technical data

Analog outputs

Current output signal	0 mA ... 20 mA
	4 mA ... 20 mA
Load/output load current output	500 Ω

Standards and Regulations


Group	IIC (A, B)
	IIB, [IIIC, IIIB] (C, E, F, G)
	IIA (D)
	IIC (A, B)
	IIB, [IIIC, IIIB] (C, E, F, G)
	IIA (D)
ATEX	# II 3(1)GD Ex nA [ia Ga Da] IIC T4 Gc Sira 09ATEX2339X
IECEX	Ex nA [ia Ga Da] IIC T4 Gc IECEX SIR 10.0033X
UL, USA/Canada	Class I, Div. 2, Groups A, B, C, D

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Connection diagram



Dimensional drawing

