

## MNX UL PCM 100/60 T



Sample photo

**Order symbol:** UL PCM 100/60 T  
**Product nbr:** 6416901  
**Description:** Enclosure, PC  
**Remarks:** Smoked transparent cover

**EAN:** 6418074038173  
**EI. number:**  
 Finland: 3421656  
 Electric No. Denmark: 8212027019  
 Electric No. Italy: 7342010  
 Electric No. Sweden: 2535403

Including: Base with metric knock-outs and TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:				Accessories:	
	Length	Width	Height		
mm:	130	80	60	MIN 5	DIN-15 Mounting rail
inch:	5.1	3.1	2.4	MIN 10	DIN-15 Mounting rail
<b>Materials:</b>				MIV 5	DIN-35 Mounting rail
<b>Material:</b>	Polycarbonate				
<b>Base colour:</b>	RAL 7035 -light grey				
<b>Cover screws material:</b>	Polyamide				
<b>Cover colour:</b>	Smoked grey				
<b>Cover screws colour:</b>	Black				
<b>Gasket material:</b>	TPE				
<b>Temperatures:</b>				<b>Rating:</b>	
<b>Temperature °C (short term):</b>	-40 ... 120 °C			Ingress Protection (EN 60529): IP66/IP67	
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			Impact Resistance (EN 62262): IK08	
<b>Temperature °F (short term):</b>	-40 ... 250 °F			Electrical insulation: Totally insulated	
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			Halogen free (DIN/VDE 0472, Part 815): 1	
<b>Accessories:</b>				UV resistance: UL 508	
MIV 100	Mounting plate (Galvanized steel)			Flammability Rating: UL 746C 5"	
				Glow Wire Test (IEC 695-2-1) °C: 960	
				NEMA Class: NEMA 1, 4, 4X, 6	
				<b>Certificates:</b>	
				SGS Fimko	

