

Self-Laminating Wire Marker Dispenser

- Self-laminating labels are provided in handy dispenser which protects markers when not in use
- Clear section of marker overlaminates and protects write-on legend
- Quick, easy to use for smaller installations and maintenance



Material Chart

| Material | Print Method | Temperature Range | Features |
|---------------------------------------|--------------|--------------------------------|--|
| Self-Laminating Vinyl, White Print-On | Pre-Printed | -40°F to 150°F (-40°C to 66°C) | Indoor/outdoor rated; thin and conformable; preferred material for most general wire/cable labeling. |

| Part Number | Part Description | Width | | Length | | Print-On Height | | Min. Cable O.D. | | Max. Cable O.D. | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|----------------------|--|-------|-------|--------|-------|-----------------|-------|-----------------|------|-----------------|-------|----------------|----------------|
| | | In. | mm | In. | mm | In. | mm | In. | mm | In. | mm | | |
| Dispenser Kit | | | | | | | | | | | | | |
| S100X125VARY | (1) Dispenser. (1) Roll, white write-on, vinyl label, 200/roll. (1) PFX-0 pen. | 1.00 | 25.40 | 1.25 | 31.75 | 0.38 | 9.65 | 0.12 | 3.07 | 0.28 | 7.03 | 1 | 10 |
| S100X225VARY | (1) Dispenser. (1) Roll, white write-on, vinyl label, 100/roll. (1) PFX-0 pen. | 1.00 | 25.40 | 2.25 | 57.15 | 0.75 | 19.05 | 0.24 | 6.06 | 0.48 | 12.13 | 1 | 10 |
| Refill Rolls | | | | | | | | | | | | | |
| S100X125VAFY | Replacement roll. White write-on, vinyl label, 200/roll. | 1.00 | 25.40 | 1.25 | 31.75 | 0.38 | 9.65 | 0.12 | 3.07 | 0.28 | 7.03 | 1 | 10 |
| S100X225VAFY | Replacement roll. White write-on, vinyl label 100/roll. | 1.00 | 25.40 | 2.25 | 57.15 | 0.75 | 19.05 | 0.24 | 6.06 | 0.48 | 12.13 | 1 | 10 |

Can be clearly identified with Panduit permanent marking pens shown on page E5.19.

Pre-Printed Clip-On Wire Markers

- Non-adhesive markers grip tightly to wire/cable
- Markers supplied on application wand tool
- Chevron cut keeps multiple markers aligned
- Black legend is embossed into wire marker clip



Material Chart

| Material | Print Method | Temperature Range | Features |
|---------------------|--------------|--------------------------------|--|
| Non-Adhesive Acetal | Pre-Printed | -22°F to 194°F (-30°C to 90°C) | Indoor/outdoor rated; durable material that has excellent resiliency to oils and solvents. |

| Part Number | Legend | No. of Markers Per Wand | Markers Per Pkg. | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|--------|-------------------------|------------------|----------------|----------------|
|-------------|--------|-------------------------|------------------|----------------|----------------|

Wire/Cable Diameter 0.08" – 0.10" (2.00mm – 2.50mm)

| | | | | | |
|--|----------------|----|-----|---|----|
| PCA07-A thru PCA07-Z | A thru Z | 30 | 300 | 1 | 10 |
| PCA07-A-J | A-J | | | 1 | 10 |
| PCA07-K-T | K-T | | | 1 | 10 |
| PCA07-U-Z | U-Z | | | 1 | 10 |
| PCA07-0 thru PCA07-9 | 0 thru 9 | | | 1 | 10 |
| PCA07-0-9 | 0-9 | | | 1 | 10 |
| PCA07-MIN | — | | | 1 | 10 |
| PCA07-PLS | + | | | 1 | 10 |

Table continues on page E3.12

Pre-Printed Clip-On Wire Markers (continued)

| |
|---------------------------------------|
| A. System Overview |
| B1. Cable Ties |
| B2. Cable Accessories |
| B3. Stainless Steel Ties |
| C1. Wiring Duct |
| C2. Surface Raceway |
| C3. Abrasion Protection |
| C4. Cable Management |
| D1. Terminals |
| D2. Power Connectors |
| D3. Grounding Connectors |
| E1. Labeling Systems |
| E2. Labels |
| E3. Pre-Printed & Write-On Markers |
| E4. Permanent Identification |
| E5. Lockout/Tagout & Safety Solutions |
| F. Index |

| Part Number | Legend | No. of Markers Per Wand | Markers Per Pkg. | Std. Pkg. Qty. | Std. Ctn. Qty. | | |
|--|------------|-------------------------|------------------|----------------|----------------|---|----|
| Wire/Cable Diameter 0.11" – 0.13" (2.80mm – 3.30mm) | | | | | | | |
| PCA11-A thru PCA11-Z | A thru Z | 30 | 300 | 1 | 10 | | |
| PCA11-A-J | A-J | | | 1 | 10 | | |
| PCA11-K-T | K-T | | | 1 | 10 | | |
| PCA11-U-Z | U-Z | | | 1 | 10 | | |
| PCA11-0 thru PCA11-9 | 0 thru 9 | | | 1 | 10 | | |
| PCA11-0-9 | 0-9 | | | 1 | 10 | | |
| PCA11-MIN | — | | | 1 | 10 | | |
| PCA11-PLS | + | | | 1 | 10 | | |
| Wire/Cable Diameter 0.13" – 0.15" (3.30mm – 3.80mm) | | | | | | | |
| PCA13-A thru PCA13-Z | A thru Z | | | 30 | 300 | 1 | 10 |
| PCA13-A-J | A-J | 1 | 10 | | | | |
| PCA13-K-T | K-T | 1 | 10 | | | | |
| PCA13-U-Z | U-Z | 1 | 10 | | | | |
| PCA13-0 thru PCA13-9 | 0 thru 9 | 1 | 10 | | | | |
| PCA13-0-9 | 0-9 | 1 | 10 | | | | |
| PCA13-MIN | — | 1 | 10 | | | | |
| PCA13-PLS | + | 1 | 10 | | | | |
| Wire/Cable Diameter 0.19" – 0.23" (4.80mm – 5.80mm) | | | | | | | |
| PCA18-A thru PCA18-Z | A thru Z | 30 | 300 | | | 1 | 10 |
| PCA18-A-J | A-J | | | 1 | 10 | | |
| PCA18-K-T | K-T | | | 1 | 10 | | |
| PCA18-U-Z | U-Z | | | 1 | 10 | | |
| PCA18-0 thru PCA18-9 | 0 thru 9 | | | 1 | 10 | | |
| PCA18-0-9 | 0-9 | | | 1 | 10 | | |
| PCA18-MIN | — | | | 1 | 10 | | |
| PCA18-PLS | + | | | 1 | 10 | | |
| Wire/Cable Diameter 0.23" – 0.37" (5.80mm – 9.40mm) | | | | | | | |
| PCA23-A thru PCA23-Z | A thru Z | | | 20 | 60 | 1 | 10 |
| PCA23-A-D | A-D | 80 | 1 | | 10 | | |
| PCA23-E-H | E-H | | 1 | | 10 | | |
| PCA23-I-L | I-L | | 1 | | 10 | | |
| PCA23-M-P | M-P | | 1 | | 10 | | |
| PCA23-Q-T | Q-T | 60 | 1 | | 10 | | |
| PCA23-U-X | U-X | | 1 | | 10 | | |
| PCA23-Y-Z | Y-Z, +, - | | 1 | | 10 | | |
| PCA23-0 thru PCA23-9 | 0 thru 9 | 80 | 1 | | 10 | | |
| PCA23-0-3 | 0-3 | | 1 | | 10 | | |
| PCA23-4-7 | 4-7 | | 1 | 10 | | | |
| PCA23-8-9 | 8, 9, +, - | | 1 | 10 | | | |
| PCA23-MIN | — | 60 | 1 | 10 | | | |
| PCA23-PLS | + | | 1 | 10 | | | |