



Hospital-Grade Power Cord, NEMA 5-15P to Locking IEC C13 - Green Dot, 10A, 125V, 18 AWG, 10 ft., Black

MODEL NUMBER: P006-L10-HG10











Connects a PC, printer, monitor, scanner or other hospital equipment with a C14 inlet to a grounded hospital-grade AC outlet.

Features

Hospital-Grade Power Cable is a Safe Solution for Medical Facilities

This hospital-grade IEC power cord is designed for computers, mobile carts, printers, scanners, monitors and other compatible equipment with a three-pin C14 inlet in a hospital or other medical facility. It features a locking C13 end for connecting to a device and a NEMA 5-15P-HG plug for connecting to a hospital-grade AC power source located outside patient care vicinities. The 10-foot length allows you great flexibility in placing equipment with respect to the power outlet.

Locking C13 Connector Helps Prevent Accidental Disconnection and Expensive Downtime
Having a cable come loose accidentally can mean the loss of power and costly downtime. The locking
C13 connector helps you avoid such danger, protecting critical equipment by maintaining a secure link
without failure. The locking cable is also invaluable when moving equipment in a rack or removing
equipment from tight areas, ensuring the power cord always stays connected.

Lifetime Warranty

The P006-L10-HG10 is backed by a lifetime warranty, ensuring reliability and performance.

Highlights

- Recommended for connecting devices to power outlets outside patient care vicinities
- 10 ft. length allows great flexibility in placing devices in relationship to AC outlet
- Hospital-grade power cable replaces or upgrades power cord provided by manufacturer
- NEMA 5-15P-HG plug connects to AC power; C13 plug connects to device's C14 inlet
- Locking C13 connector maintains secure link to avoid loss of power and costly downtime

Applications

- Connect a mobile cart battery, monitor, computer or printer to a hospital-grade surge protector up to 10 ft. away in a hospital environment outside patient care vicinities
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

P006-L10-HG10 Hospital-Grade
 Power Cord, NEMA 5-15P to
 Locking IEC C13, 10 ft., Black

Specifications

OVERVIEW





| UPC Code | 037332224705 |
|---------------------------------|--|
| Country/Region | North America |
| | |
| INPUT | |
| Maximum Input Amps | 10 |
| Cable Length (ft.) | 10 |
| Cable Length (m) | 3 |
| Cable Length (in.) | 120 |
| Voltage Compatibility (VAC) | 125 |
| PHYSICAL | |
| Power Cord Jacket Type | SJT |
| Wire Gauge (AWG) | 18 |
| Wire Gauge (OD - mm²) | 0.82 |
| Shipping Dimensions (hwd / in.) | 12.80 x 8.86 x 0.50 |
| Shipping Dimensions (hwd / cm) | 32.51 x 22.50 x 1.27 |
| Shipping Weight (lbs.) | 0.80 |
| Shipping Weight (kg) | 0.36 |
| Color | Black |
| Number of Conductors | 3 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4 to 221 F (-20 to 105 C) |
| Storage Temperature Range | -4 to 221 F (-20 to 105 C) |
| Relative Humidity | 0-65% RH |
| CONNECTIONS | |
| Side A - Connector 1 | NEMA 5-15P-HG |
| Side B - Connector 1 | IEC-320-C13 - LOCKING |
| SPECIAL FEATURES | |
| | No |
| High Voltage | No No |
| Heavy-Duty | |
| Locking Plug | Yes |
| CERTIFICATIONS | |
| Certifications | ANSI/UL 62 and 817, CAN/CSA C22.2 NO. 21 and 49, RoHS, REACH |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

| WARRANTY | |
|--|---------------------------|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies