


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NO. *	BUNDLE DIA.		A	B	C	D	E	F	MIN. LOOP TENSILE lbs. (N)	CROSS SECTION	TIP STYLE	WEIGHT lbs./100 pcs. (g)
	MIN. in (mm)	MAX. in (mm)										
PLT2H	.188 (4.8)	2.00 (51)	.075 (1.9)	.300 (7.6)	.338 (8.6)	.290 (7.4)	.480 (12.2)	8.1 (206)	120 (534)	HEAVY	STRAIGHT	.76 (346)
PLT2.5H	.188 (4.8)	2.50 (64)	.075 (1.9)	.300 (7.6)	.338 (8.6)	.290 (7.4)	.480 (12.2)	9.8 (251)	120 (534)	HEAVY	STRAIGHT	.90 (408)
PLT3H	.188 (4.8)	3.00 (76)	.075 (1.9)	.300 (7.6)	.338 (8.6)	.290 (7.4)	.480 (12.2)	11.4 (290)	120 (534)	HEAVY	STRAIGHT	1.04 (472)
PLT4H	.188 (4.8)	4.00 (102)	.075 (1.9)	.300 (7.6)	.338 (8.6)	.290 (7.4)	.480 (12.2)	14.5 (368)	120 (534)	HEAVY	STRAIGHT	1.28 (581)
PLT5H	.188 (4.8)	5.00 (127)	.078 (2.0)	.350 (8.9)	.406 (10.1)	.340 (8.6)	.560 (14.2)	17.7 (450)	175 (778)	HEAVY	STRAIGHT	2.06 (934)
PLT6H	.188 (4.8)	6.00 (152)	.078 (2.0)	.350 (8.9)	.406 (10.1)	.340 (8.6)	.560 (14.2)	20.9 (530)	175 (778)	HEAVY	STRAIGHT	2.46 (1116)
PLT8H	.188 (4.8)	9.00 (229)	.078 (2.0)	.350 (8.9)	.406 (10.3)	.340 (8.6)	.560 (14.2)	30.6 (779)	175 (778)	HEAVY	STRAIGHT	3.36 (1524)
PLT13H	5.50 (140)	13.00 (330)	.078 (2.0)	.350 (8.9)	.406 (10.3)	.340 (8.6)	.560 (14.2)	43.3 (1100)	175 (778)	HEAVY	STRAIGHT	4.59 (2080)

NOTE:

*SEE www.panduit.com FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE, PART MATERIAL, PART COLOR AND ANY THIRD PARTY RECOGNITION OR COMPLIANCE.

DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS

REV						DATE		BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY		DATE	CHK	SCALE	DRAWING NUMBER		SIZE	
10						4/04/14		BWG	MPH	JADE	UPDATED NOTES.	SS-5540/10	CEW		12-27-84		HVP	NONE	SS-5540 SHEET 4		A
09						8/13/13		BWG	KJM	RTFI	UPDATED TITLE BORDER.	SS-5540/09							SHT 1 OF 1		

TITLE
PAN-TY CABLE TIES - PLT SERIES

CUSTOMER DRAWING

ITEM REVISION NAME
W10001CD/10

DATASET FILE NAME
W10001CD/10-SS-5540 SH4 PLT SERIES CUSTOMER

MATERIAL:
NYLON 6.6

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]
 .x ± .02 [.5] .xxx ± .020 [.51]
 ANGLES ±

THIRD ANGLE PROJECTION

D10100DA/16