

MNX UL PCM 100/75 G



Sample photo

Order symbol: UL PCM 100/75 G
Product nbr: 6416302
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074024480
El. number:
 Finland: 3422259
 Electric No. 8212026984
 Denmark:
 Electric No. Sweden: 2535304

Including: Base with metric knock-outs and TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:		Length	Width	Height	Accessories:			
mm:		130	80	75	MIN 5	DIN-15 Mounting rail		
inch:		5.1	3.1	3.0	MIN 10	DIN-15 Mounting rail		
Materials:								
Material:	Polycarbonate					MIV 5	DIN-35 Mounting rail	
Base colour:	RAL 7035 -light grey					MIV 10	DIN-35 Mounting rail	
Cover screws material:	Polyamide					FP A 100/130	Front plate (Aluminium)	
Cover colour:	RAL 7035 -light grey					HFP 130	Front plate hinge series	
Cover screws colour:	Grey					FP 22046	Wall fastening lug (4 pcs)	
Gasket material:	TPE					Rating:		
Temperatures:							Ingress Protection (EN 60529): IP66/IP67	
Temperature °C (short term):	-40 ... 120 °C					Impact Resistance (EN 62262): IK08		
Temperature °C (continuous):	-40 ... 80 °C					Electrical insulation: Totally insulated		
Temperature °F (short term):	-40 ... 250 °F					Halogen free (DIN/VDE 0472, Part 815): 1		
Temperature °F (continuous):	-40 ... 175 °F					UV resistance: UL 508		
Accessories:							Flammability Rating: UL 746C 5"	
MIV 100	Mounting plate (Galvanized steel)					Glow Wire Test (IEC 695-2-1) °C: 960		
							NEMA Class: NEMA 1, 4, 4X, 6	
							Certificates:	
							SGS Fimko	

