





UPC Code: 07847779702
Country Of Origin: Mexico

NEMA: L6-15R



4560

Brand Features

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

Item Description

15 Amp, 250 Volt, NEMA L6-15R, 2P, 3W, Single Locking Receptacle, Industrial Grade, Grounding - BLACK

Technical Information

AC Horsepower Ratings
At Rated Voltage: 1-1/2 HP

Electrical Specifications
Grounding: Grounding
Amperage: 15 Amp
Voltage: 250 Volt

Pole: 2 Wire: 3

Dielectric Voltage: Withstands 2000V

per UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications
Flammability: Rated V-2 per UL94
Operating Temperature: -40C to 60C

Material Specifications
Face Material: Nylon
Body Material: Nylon

Environment: Dry

Line Contacts: Brass .031 Thick Terminal Screws: Brass 10-32 Grounding Screw: Brass 8-32 Yoke: Zinc-Plated Steel

Strap Material: Nickel-Plated Brass

Color: Black

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: 18-10 AWG **Product ID:** Ratings and NEMA I.D. permanently marked on device

Termination: Side

Product Features

NEMA: L6-15R

Color: Black

Device Type: Locking Receptacle

Standards and Certifications

NEMA: WD-6 ANSI: C-73


UL498: File E13399

UL Fed Spec WC-596: File E13399 **CSA C22.2 No. 42**: File LR-406


NOM: 057

Warranty: Lifetime Warranty

Dimensional Diagram



Wiring Diagram



L6-15R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:telefono: optimization} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

