

Valve connectors - SACC-V-3CON-PG9/B-1L-SV 24V - 1528002

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Valve connectors, 3-position, Valve connector B (10 mm), with 1 LED, connected with Varistor, Screw connection, cable gland Pg9, external cable diameter 6 mm ... 8 mm



Key Commercial Data

Packing unit	1 pc
GTIN	4 017918 981075
GTIN	4017918981075

Technical data

Dimensions

External diameter	6 mm 8 mm
Ambient conditions	
Ambient temperature (operation)	-25 °C 85 °C (valve plug)
Degree of protection	IP65

General

Rated current at 40°C	10 A
Rated voltage	24 V
Number of positions	3
Insulation resistance	\geq 100 MΩ
Status display	1 LED
Protective circuit/component	Varistor
Overvoltage category	Ш
Degree of pollution	3
Connection method	Screw connection
Conductor cross section	0.34 mm ² 1.5 mm ²
Conductor cross section AWG	22 16
Insertion/withdrawal cycles	50 (Valve connector)

06/11/2019 Page 1 / 2



Valve connectors - SACC-V-3CON-PG9/B-1L-SV 24V - 1528002

Technical data

Material

Flammability rating according to UL 94	НВ
Valve plug contact material	CuZn
Valve plug contact surface material	Ni
Valve plug contact insert material	PA6
Material housing valve plug	PA6
Sealing material	NBR

Standards and Regulations

Flammability rating according to UL 94	HB

EHC

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC

RU C-DE.AI30.B.01102

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com