5-228618-2 <

COAXICON

TE Internal #: 5-228618-2 Coax, Pin Contact, 1 Position, Wire & Cable, Straight, RG 179 / RG 179A / RG 187A, Gold, 1 A, Power & Signal, -55 – 125 °C [-67 – 257 ° F]

View on TE.com >

Connectors > Contacts > RF Contacts



RF Contact Style: Coax

Contact Type: Pin

Number of Positions: 1

Connector & Contact Terminates To: Wire & Cable

Contact Orientation: Straight

Features

Other

Dielectric Material

PTFE

Electrical Characteristics

Impedance Options

Non-Matched



Body Features

Shell Plating Material	Gold
Shell Base Material	Brass
	30 µin
Packaging Features	
Packaging Method	Carton
Contact Features	
	30 µin
Contact Base Material	Beryllium Copper
Contact Type	Pin
Contact Orientation	Straight
Contact Mating Area Plating Material	Gold
Contact Mating Retention	Without
Contact Current Rating (Max)	1 A

Product Type Features

5-228618-2

Coax, Pin Contact, 1 Position, Wire & Cable, Straight, RG 179 / RG 179A / RG 187A, Gold, 1 A, Power & Signal, -55 – 125 °C [-67 – 257 °F]



RF Contact Style	Coax
Connector & Contact Terminates To	Wire & Cable
Compatible With RF Cable Type	RG 187A, RG 179B, RG 187, RG 179A, RG 179
Configuration Features	
Number of Positions	1
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Candidate List Declared Against: JAN 2024

(240)

SVHC > Threshold:

Pb (4% in Contact/Component)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Yet Reviewed for halogen content

Not applicable for solder process capability

5-228618-2

Coax, Pin Contact, 1 Position, Wire & Cable, Straight, RG 179 / RG 179A / RG 187A, Gold, 1 A, Power & Signal, -55 – 125 °C [-67 – 257 °F]



Compatible Parts



Customers Also Bought



TE Part #1-1375820-8 TE Part #1-87631-2 CST-100 II HOUSING 18 POS 16 MODIV HSG DR MRKD .100 POL	TE Part #5-228596-1 TE Part #58430-1 SOCKET,STR,SIZE 8,AMPLIMITE TOOL, REPAIR
---	---



Documents

Product Drawings PIN,STRAIGHT,SIZE 8,AMPLIMITE English CAD Files 3D PDF

3D

5-228618-2

Coax, Pin Contact, 1 Position, Wire & Cable, Straight, RG 179 / RG 179A / RG 187A, Gold, 1 A, Power & Signal, -55 – 125 °C [-67 – 257 °F]



Customer View Model

ENG_CVM_CVM_5-228618-2_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-228618-2_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-228618-2_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.