# 861648-1 ACTIVE

### LGH

TE Internal #: 861648-1

Lead Assembly, 27000 VDC, Wire-to-Panel, 7 Position, Wire & Cable, Plug, Pin, Panel Mount, -55 – 125 °C [-67 – 257 °F], Circular

Power Connectors

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors



EU RoHS Compliance: Compliant with Exemptions
EU ELV Compliance: Compliant with Exemptions

Connector Product Type: Lead Assembly

Operating Voltage: **27000 VDC**Connector System: **Wire-to-Panel** 

## **Features**

#### Other

EU RoHS Compliance	Compliant with Exemptions
EU ELV Compliance	Compliant with Exemptions
Product Type Features	
Connector Product Type	Lead Assembly
Connector System	Wire-to-Panel
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Plug
Configuration Features	
Number of Positions	7
Electrical Characteristics	
Operating Voltage	27000 VDC
Body Features	
Positive Stop Ferrule	Without
Contact Features	
Contact Type	Pin

Without

**Contact Protection** 



#### Mechanical Attachment

Panel Mount Feature Type	Retaining Ring
Mating Alignment	With
Connector Mounting Type	Panel Mount
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Shielded	No
	No
Shielded	No 1

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (2.5% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Customers Also Bought



TE Part #5102321-4

A/L UNIV HDR 20P VERT LG LAT



TE Part #36158
TERMINAL, PIDG R 16-14 6



TE Part #640925-1 RECEPT,PIDG FASTON 22-18 110






TE Part #3-643817-9
09P MTA156 CONN ASSY 18AWG LF



TE Part #350706-1 UMNL SPLIT PIN 24-18 PTPBR L/P



TE Part #644752-3
03P MTA156 HDR ASSY SQ STR F/L





TE Part #3-644894-4
04P CST100 SHRD HDR ASSY LF



## **Documents**

**Product Drawings** 

PLUG ASS'Y H.V. 7 PIN

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_861648-1\_M.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_861648-1\_M.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_861648-1\_M.3d\_stp.zip

English

Lead Assembly, 27000 VDC, Wire-to-Panel, 7 Position, Wire & Cable, Plug, Pin, Panel Mount, -55 – 125 °C [-67 – 257 °F], Circular Power Connectors



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Instruction Sheets** 

Instruction Sheet (U.S.)

English