

Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT1.5I-M

Pan-Ty® locking tie, intermediate cross section, 5.6" (142mm) length, nylon 6.6, natural, bulk package.

Specs

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

Std. Pkg. Qty.	1000
Material	Nylon 6.6
Color	Natural
Cross Section	Intermediate
Length (In.)	5.6
Length (mm)	142
Locking Style	Locking
Width (In.)	0.142
Width (mm)	3.6
Min. Loop Tensile Strength Lbs. (N)	40 (178)
Plenum-Rated	Yes, AH-2
Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
Length In (mm)	5.6 (142)
Thickness In (mm)	0.045 (1.1)
Bundle Diameter Range In. (mm)	0.06 (1.5) - 1.38 (35)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	MS3367-5-9
UL 62275 Compliant (Type 1, 11)	—
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Operating Temperature	-76°F (-60°C) - 185°F (85°C)
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
Releasable	No
RoHS Compliancy Status	Compliant

Min. Order Qty.

1,000.0000