

**H4,0/20DS GR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- Polypropylene conical cable entry funnel
- Heat-resistant up to 105°C

For conductors from 0.5 – 10.0 mm<sup>2</sup> (AWG 20-7)

Material: E-Cu, tin galvanised

Dimensional tolerance acc. to DIN 46228 sect. 4

**General ordering data**

|            |  |
|------------|--|
| Version    | Wire-end ferrule, Standard, 15 mm, 12 mm, grey |
| Order No.  | <a href="#">9203630000</a>                     |
| Type       | H4,0/20DS GR                                   |
| GTIN (EAN) | 4032248565078                                  |
| Qty.       | 500 pc(s).                                     |
| Packaging  | loose  |

Creation date September 18, 2022 4:44:08 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

**H4,0/20DS GR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight 0.26 g

**Technical data**

|                        |  |         |          |
|------------------------|--|---------|----------|
| Description of article | Wire end ferrule with plastic collar, special size, grey | Version | Standard |
|------------------------|--|---------|----------|

**Wire-end ferrules**

|                             |                   |   |               |
|-----------------------------|-------------------|---|---------------|
| Collar diameter (D2)        | 4.7 mm            | Colour code                             | Miscellaneous |
| Conductor cross-section     | 4 mm <sup>2</sup> | Contact surface diameter (D1)           | 2.9 mm        |
| Contact surface length (L2) | 12 mm             | L1 in mm                                | 20 mm         |
| Metal sleeve thickness (S1) | 0.2 mm            | Plastic collar thickness (S2)           | 0.5 mm        |
| Stripping length            | 15 mm             | Wire connection cross section AWG, max. | AWG 12        |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 | ECLASS 12.0 | 27-40-02-01 |

**Approvals**

Approvals



ROHS Conform

**Downloads**

|                    |  |
|--------------------|--|
| Engineering Data   | <a href="#">WSCAD, EPLAN</a>   |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>   |
| Brochures          |  |

**Data sheet**

**H4,0/20DS GR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Weidmuller:](#)

[9203630000](#)