

GREASE LUBRICATION SCHEDULE FOR HORIZONTAL SHAFT APPLICATIONS

REX® 2000, 3000 & 6000 SERIES ROLLER BEARING UNITS

SHAFT DIAM.	GREASE AMOUNT	<u>6 MONTHS RELUBE</u>	<u>4 MONTHS RELUBE</u>	<u>2 MONTHS RELUBE</u>	<u>1 MONTH RELUBE</u>	<u>2 WEEKS RELUBE</u>
3/4 - 1	0.20 oz.	1400	2200	3400	5000	6500
1-1/8 - 1-1/4	0.25 oz.	1150	1800	2800	4500	5750
1-7/16 - 1-1/2	0.30 oz.	1000	1550	2400	3800	5250
1-11/16 - 1-3/4	0.40 oz.	870	1350	2100	3300	4450
1-15/16 - 2	0.45 oz.	700	1100	1700	2700	4050
2-3/16 - 2-1/4	0.55 oz.	630	1000	1500	2400	3650
2-3/8 - 2-1/2	0.65 oz.	580	910	1400	2250	3300
2-11/16 - 3	1.20 oz.	460	730	1100	1800	2800
3-3/16 - 3-1/2	2.00 oz.	410	640	1000	1550	2400
3-1/16 - 4	2.90 oz.	350	550	850	1350	2050
4-3/16 - 4-1/2	3.25 oz.	300	470	740	1150	1850
4-15/16 - 5	5.00 oz.	280	440	680	1050	1600

Shaft speed in rpm

- * OPERATING TEMPERATURES LIMITED TO -40 TO +225°F
- * "DIRTY", CORROSIVE OR WET ENVIRONMENTS REQUIRE MORE FREQUENT RE-LUBE.
- * MAXIMUM SPEEDS FOR TYPE "Z" SEALS
- * **REDUCE LUBRICATION INTERVALS BY HALF FOR VERTICAL SHAFT APPLICATIONS**
- * SUGGESTED GREASES ARE:
 - EXXON RONEX MP
 - TEXACO PREMIUM RB
 - SHELL ALVANIA 2
 - GULF CROWN NO. 2
 - AMOCO RYKON 2