



Home > Products > Discrete Thermistors > 197 > Product Page

### 197-102DAG-A01



Actual product appearance may vary.

**Chip thermistor with bare leads and epoxy**

#### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### Features

Accuracy  
High stability  
Long life  
Cost effective  
Small size  
Epoxy coated

#### Potential Applications

Communications  
Medical  
Fire detection  
Computers  
Instrumentation test equipment

#### Description

197 Series Thermistors are available in a broad range of custom resistance values and R/T curves. They are also available with insulated or noninsulated leads.

#### Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 °F]	1,000 Ohm
Tolerance	± 10.0%
Accuracy	25 °C [77 °F]
R- T Curve	10A
Operating Temperature Range	- 60 °C to 125 °C [ - 76 °F to 257 °F]
Maximum Diameter	2,413 mm [0.095 in]
Termination Material	32 Gauge tinned copper, alloy 180
Lead length	38,1 mm [1.50 in]
Time Constant in Air	15.0 s
Dissipation Constant	0,75 m/W°C
Series Name	197

#### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

#### Keyword Search

Search for product and support information.

All Sensing and Control

#### Product Search

Part number search:

Use (\*) to expand search

[Specification Search](#)