

# **Contact Cleaner G3®**

Contact Cleaner 1632

## Introduction

Contact Cleaner G3®<sup>™</sup> contains a patented formula designed specifically as the replacement for contact cleaners containing HCFC-141b. This precision blend is the choice for all types of cleaning of switches, relays, contact pads and other electrical connections. The innovative cleaner removes oils, greases, silicones, dirt and grim. Contact Cleaner G3® is the superior choice for all contact cleaning applications.

#### Features / Benefits

Non-Ozone Depleting Non-Flammable Safe on Most Plastics Rapidly Evaporating Zero Residue

### **Chemical Components**

1,2-transdichloroethylene 1,1,1,3,3-Pentafluoropropane		30-90% 10-50%
Ethyl Hydroxy Propionate	(97-64-3	<1%
1,1,1,2-Tetraflouroethane (Propellant)	.(871-97-2)	10-20%
Carbon Dioxide (Propellant)	. (124-38-9)	1-10%

#### **Solvent Specifications**

Snap Approved	Non- Flammable	Toxicity Exposure (ppm)	Relative Evaporation Rate TCE=1	Surface Tension (dyne/cm)	Cleaning Efficiency 1=Relative efficiency of 141b*	VOC Content (grams/liter)	ODP
Yes	Yes	200	0.75	21.0	1.33	1001	0

\*Cleaning Efficiency in compliance with MIL-PRF-29608(AS)

### **Plastic Compatibility**

Material	Compatibility	Material	Compatibility
ABS	Not Compatible	PMMA	Not Compatible
Nylon	Excellent	POM	Excellent
Lexan	Not Compatible	PP	Excellent
HDPE	Excellent	PS	Not Compatible
CDPE	Excellent	PTFE	Excellent
C. E. Phenolic	Excellent	PVC	Excellent

<b>Environmental Policy</b>			
	Techspray® is committed to developing environment. We will continue to meet a state and local government agencies.	products to ensure a safer and cleaner and sustain the regulations of all federal,	
Licensing Restriction			
	The use of this product for cleaning is subject to U.S. Patent No. 5,902,412 and use is restricted by Tech Spray, L. P.		
Packaging and Availat	bility		
	Contact Cleaner G3® is available in the following size:		
	1632-16S 16 Ounce Aerosol		
Resources			
	Techspray® products are supported by a services resources.	a global sales, technical and customer	
	For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at www.techspray.com.		
North America Tech Spray L.P. P.O. Box 949 Amarillo, TX 79105 800-858-4043 email: tsales@techspray.com	<b>Europe</b> Techspray International UNIT 4, 44/46 Bunyan Road, Kempston Bedford MK42 8HL United Kingdom +44 (0) 1234 855443 email: tseurope@techspray.com	<b>Countries Outside US</b> Call to locate a distributor in your country.	

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P. P.O. Box 949 Amarillo, TX 79105 www.techspray.com

English MSDS French MSDS German MSDS Italian MSDS Spanish MSDS



Copyright 2004 Tech Spray, L. P. For Commercial Use Only