

**VPK (blanking plug in plastic)
VP 36-K54**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



For sealing surplus threaded holes to maintain the IP class of protection

General ordering data

Type	VP 36-K54
Order No.	0501260000
Version	VPK (blanking plug in plastic), Blanking plug, PG 36, 10 mm, IP65, Polyamid 6 (PA6 - GF30)
GTIN (EAN)	4008 190020972
Qty.	10 pc(s).

Creation date August 16, 2020 7:33:09 PM CEST

Catalogue status 24.07.2020 / We reserve the right to make technical changes.

Data sheet

**VPK (blanking plug in plastic)
VP 36-K54**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	14 mm	Length (inches)	0.551 inch
Net weight	10.4 g		

General information

Material	Polyamid 6 (PA6 - GF30)	Cable glands	PG
External thread	PG 36	Length of thread	10 mm
Protection degree	IP54	Protection degree with GWDR	IP65
Operating temperature range, min.	-40 °C	Operating temperature range, max.	100 °C
Head diameter	55 mm	UL 94 flammability rating	V-2
Halogen	No		

Classifications

ETIM 6.0	EC000451	ETIM 7.0	EC000451
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-33
eClass 10.0	27-14-44-25	UNSPSC	30-21-18-01

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN_WSCAD
Engineering Data	STEP

Data sheet

**VPK (blanking plug in plastic)
VP 36-K54**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

