




RIGID THREADED HUBS - DIE CAST ZINC

Conduit Hub, Insulated Throat Die Cast Zinc

B33



Catalog #: 1708

APPLICATIONS

For use with threaded rigid/IMC conduit to connect and bond conduit to a threadless opening in a box or enclosure
May be used in wet or dry locations

PRODUCT FEATURES

Rugged metallic construction insures mechanical protection
Insulated throat protects wires and reduces wire pulling effort
O-ring seals the assembly and provides a raintight seal

UL LISTED

Standard 514B, UL Listed E195969

CSA

C22.2 No. 18

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO MSDS for WP Boxes and Fittings, January 2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size: 2 in.

DRAWING DIMENSIONS

Dimension A: 1.895 in.
Dimension B: 3.236 in.
Dimension C: 2 in. - 11-1/2 NPT

PACKAGING

Package Type: Carton
Ship Carton Qty.: 10
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 92.00
Ship Carton Length (in.): 9.40
Ship Carton Width (in.): 8.60
Ship Carton Height (in.): 6.10
Ctn Weight (Lbs.): 9.20
UPC Number: 050169017081
I2of5: 50050169017086